

FS 2CO ECO**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Product image**General ordering data**

Version	D-SERIES, Relay socket, Number of contacts: 2, CO contact, Screw connection
Order No.	7760056126
Type	FS 2CO ECO
GTIN (EAN)	4032248878154
Qty.	10 pc(s).
Local product	Only available in certain countries

FS 2CO ECO

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.comwww.weidmueller.com**Technical data****General ordering data**

Local product Only available in certain countries

Dimensions and weights

Depth	30 mm	Depth (inches)	1.181 inch
Height	75 mm	Height (inches)	2.953 inch
Width	22 mm	Width (inches)	0.866 inch
Net weight	36 g		

Rated data UL

Certificate No. (cURus) E355547

General data

Rail TS 35

Further details of approvals / standards

Certificate No. (cURus) E355547

Connection data

Wire connection method Screw connection

Classifications

ETIM 6.0	EC001456	ETIM 7.0	EC001456
ETIM 8.0	EC001456	ECLASS 9.0	27-37-16-03
ECLASS 9.1	27-37-16-03	ECLASS 10.0	27-37-16-03
ECLASS 11.0	27-37-16-03	ECLASS 12.0	27-37-16-03

Approvals

Approvals



ROHS Conform

UL File Number Search UL Website

Certificate No. (cURus) E355547

DownloadsApproval/Certificate/Document of Conformity [EU Konformitätserklärung / EU Declaration of Conformity](#)
[EU Declaration of Conformity](#)

FS 2CO ECO

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

Mating connector (fully pluggable)

with LED

Relay from the D-SERIES DRE www.weidmueller.com

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Integrated with test button (AC red, DC blue)
- Integrated with status display (AC red, DC green) and/or free-wheel diode

General ordering data

Type	DRE270048L	Version
Order No.	7760054274	D-SERIES DRE, Relay, Number of contacts: 2, CO contact, Ag alloy,
GTIN (EAN)	6944169719820	Rated control voltage: 48 V DC, Continuous current: 5 A, Plug-in
Qty.	20 pc(s).	connection
Type	DRE270110L	Version
Order No.	7760054275	D-SERIES DRE, Relay, Number of contacts: 2, CO contact, Ag alloy,
GTIN (EAN)	6944169719837	Rated control voltage: 110 V DC, Continuous current: 5 A, Plug-in
Qty.	20 pc(s).	connection
Type	DRE270615L	Version
Order No.	7760054278	D-SERIES DRE, Relay, Number of contacts: 2, CO contact, Ag alloy,
GTIN (EAN)	6944169719868	Rated control voltage: 115 V AC, Continuous current: 5 A, Plug-in
Qty.	20 pc(s).	connection
Type	DRE270012L	Version
Order No.	7760054272	D-SERIES DRE, Relay, Number of contacts: 2, CO contact, Ag alloy,
GTIN (EAN)	6944169719806	Rated control voltage: 12 V DC, Continuous current: 5 A, Plug-in
Qty.	20 pc(s).	connection
Type	DRE270524L	Version
Order No.	7760054276	D-SERIES DRE, Relay, Number of contacts: 2, CO contact, Ag alloy,
GTIN (EAN)	6944169719844	Rated control voltage: 24 V AC, Continuous current: 5 A, Plug-in
Qty.	20 pc(s).	connection
Type	DRE270730L	Version
Order No.	7760054279	D-SERIES DRE, Relay, Number of contacts: 2, CO contact, Ag alloy,
GTIN (EAN)	6944169719875	Rated control voltage: 230 V AC, Continuous current: 5 A, Plug-in
Qty.	20 pc(s).	connection
Type	DRE270024L	Version
Order No.	7760054273	D-SERIES DRE, Relay, Number of contacts: 2, CO contact, Ag alloy,
GTIN (EAN)	6944169719813	Rated control voltage: 24 V DC, Continuous current: 5 A, Plug-in
Qty.	20 pc(s).	connection
Type	DRE270548L	Version
Order No.	7760054277	D-SERIES DRE, Relay, Number of contacts: 2, CO contact, Ag alloy,
GTIN (EAN)	6944169719851	Rated control voltage: 48 V AC, Continuous current: 5 A, Plug-in
Qty.	20 pc(s).	connection

FS 2CO ECO

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

Mating connector (fully pluggable)

with LED and free-wheel diode



Relay from the D-SERIES DRE www.weidmueller.com

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Integrated with test button (AC red, DC blue)
- Integrated with status display (AC red, DC green) and/or free-wheel diode

General ordering data

Type	DRE270024LD	Version
Order No.	7760054280	D-SERIES DRE, Relay, Number of contacts: 2, CO contact, Ag alloy,
GTIN (EAN)	6944169719882	Rated control voltage: 24 V DC, Continuous current: 5 A, Plug-in
Qty.	20 pc(s).	connection