

CA-T2T2-7.5M-22/3-R-BBG**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

**General ordering data**

Version	AC charging cable, Plug type - charging point: Type 2, Plug type - vehicle side: Type 2, Charging power, max.: 22 kW, Number of phases: 3, Rated current: 32 A, Cable length: 7.5 m, Cable type: regular
Order No.	2791300000
Type	CA-T2T2-7.5M-22/3-R-BBG
GTIN (EAN)	4064675070771
Qty.	1 pc(s).

CA-T2T2-7.5M-22/3-R-BBG

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.comwww.weidmueller.com**Technical data****Dimensions and weights**

Net weight 4,580 g

Temperatures

Storage temperature -40 °C...70 °C

Operating temperature -30 °C...55 °C

Operating temperature, max. 55 °C

Humidity at storage temperature 5 - 95% rel. humidity

Operating temperature, min. -30 °C

Material data

Max. relative humidity during storage 95 %

Operating temperature, min. -30 °C

Storage temperature, min. -40 °C

Operating temperature, max. 55 °C

Storage temperature, max. 70 °C

System requirementsType of communication to vehicle Control Pilot (CP),
Proximity Pilot / Plug
Present (PP)**Features**

Protection degree IP54

Housing

Protection degree IP54

Approvals and normsApprovals IEC 62196-1, IEC
62196-2, EN 50620**Classifications**

ETIM 6.0 EC002897 ETIM 7.0 EC002897

ETIM 8.0 EC002897 ECLASS 9.0 27-14-47-05

ECLASS 9.1 27-14-47-05 ECLASS 10.0 27-14-47-05

ECLASS 11.0 27-14-47-05 ECLASS 12.0 27-14-47-05

DownloadsUser Documentation [Safety notes](#)Catalogues [Catalogues in PDF-format](#)