

Basic features

Approval/Conformity	CE UKCA cULus WEEE
Basic standard	IEC 60947-5-2 IEC 60947-5-7

Display/Operation

Function indicator	Adjustment indicator
Power indicator	no

Electrical connection

Connection	M12x1-Male, 3-pin, A-coded
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Limit frequency -3 dB	500 Hz
Load resistance RL max.	500 Ohm
No-load current I _o max. at U _e	10 mA
Operating voltage U _b	10...30 VDC
Rated insulation voltage U _i	75 V DC
Rated operating voltage U _e DC	24 V
Ripple max. (% of U _e)	15 %
Slope I	4.00 mA/mm

Environmental conditions

Ambient temperature	-10...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 g _n , 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67

Functional safety

MTTF (40 °C)	640 a
--------------	-------

Interface

Analog output	Analog, current 4...20 mA
Output characteristic	falling on approach
Output current at S _I max.	20 mA
Output current at S _I min.	4 mA
Output current at S _e	12 mA

Material

Housing material	Brass, nickel-plated
Material sensing surface	PBT

Mechanical data

Dimension	Ø 18 x 44.5 mm
Installation	for flush mounting
Size	M18x1
Tightening torque	20 Nm

Inductive Sensors
BAW M18ME-ICC50B-S04G
Order Code: **BAW001U**

BALLUFF

Range/Distance

Linearity range SI	1...5 mm
Measuring range	1...5 mm

Non-linearity max.	±120 µm
Repeat accuracy per BWN	±8 µm
Temperature drift max. from end value	±5.0 %

Remarks

With connector, e.g. BKS-S 20-... total length = switch length +18 mm.

Values referenced to axial approach of St 37 target. For other materials correction factors are applied.

Load resistance RL max. applies for Ub min. 16V.

When used in Balluff clamping holders, Ua may be reduced by max. 10%.

Scattering (e.g. due to manufacturing tolerances) is described by the tolerance T at Se. This can be approximated using the formula: $T = (s_{lmax} + s_{lmin}) / 20 = \pm xx \text{ mm}$.


For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams



Technical Drawings

