

2902990

https://www.phoenixcontact.com/pc/products/2902990

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



This is an individual product; please order the complete set. The measuring transducer processes the mV signal of the upstream Rogowski coil. The measuring transducer has 8 current measuring ranges (100 A ... 4000 A AC) which can be set; max. output current of 1 A AC.

Commercial Data

Item number	2902990
Packing unit	1 pc
Minimum order quantity	1 pc
Product Key	CK4A12
GTIN	4046356703734
Weight per Piece (including packing)	147.2 g
Weight per Piece (excluding packing)	136.46 g
Customs tariff number	85437090
Country of origin	DE



2902990

https://www.phoenixcontact.com/pc/products/2902990

Technical Data

Product properties

Product type	Current transformer
--------------	---------------------

Electrical properties

Measuring transducers

Linearity error	< 0.5 % (From the range end value)
Maximum transmission error	≤ 0.5 % (From the range end value)
Frequency range	45 Hz 65 Hz
Current consumption	< 190 mA (at 19.2 V)
Test voltage	1.5 kV AC (Supply/input and output: 50 Hz, 1 min)

General

Converter type	Measuring transducer for Rogowski coil
Class	1
Can be calibrated	no

Supply: Measuring transducers

Nominal supply voltage	24 V DC -20 % +25 %
Nominal supply voltage range	19.2 V DC 30 V DC
Max. current consumption	190 mA
Power consumption	4 W

Input data

Signal

Curve type Sine Input impedance 27 k Ω (smallest measuring range)	Input signal (at 50 Hz)	100 mV (1000 A)
Input impedance 27 k Ω (smallest measuring range)	Curve type	Sine
	Input impedance	27 k Ω (smallest measuring range)

Current transformers	
Configurable/programmable	Via DIP switches
Rated power	1.5 VA
Primary rated current I _{pn}	0 A AC 100 A AC
	0 A AC 250 A AC
	0 A AC 400 A AC
	0 A AC 630 A AC
	0 A AC 1000 A AC
	0 A AC 1500 A AC
	0 A AC 2000 A AC
	0 A AC 4000 A AC
Phase angle	<1°
Can be calibrated	no
Class	1



2902990

https://www.phoenixcontact.com/pc/products/2902990

Converter type	Measuring transducer for Rogowski coil
utput data	
Signal	
Designation	Measuring transducer
Current output signal	0 A AC 1 A AC
Load	0 Ω 1.5 Ω
onnection data	
Measuring transducer side	
Connection method	Screw connection
Stripping length	7 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm² 2.5 mm²
Conductor cross section flexible	0.2 mm² 2.5 mm²
Conductor cross section AWG	24 14
Tightening torque	0.5 Nm 0.6 Nm
gnaling	
Operating voltage display	Green LED
mensions	
Width	22.5 mm
Height	85 mm
Depth	70.4 mm
Item dimensions	
Width	22.5 mm
Height	85 mm
Depth	70.4 mm
aterial specifications	
Housing material	Polyamide
nvironmental and real-life conditions	
Ambient conditions	
Measuring transducer degree of protection	IP20
Ambient temperature (operation)	-10 °C 65 °C (-14 °F 149 °F)
	-20 °C 70 °C (Measuring transducer)
	05 00 05 00 (Managination)
Ambient temperature (storage/transport)	-25 °C 85 °C (Measuring transducer)
Ambient temperature (storage/transport) Altitude	< 2000 m

Approvals



2902990

https://www.phoenixcontact.com/pc/products/2902990

UKCA	
Certificate	UKCA-compliant
CMIM	
Certificate	CMIM-compliant
Mounting	
Mounting type	DIN rail mounting



2902990

https://www.phoenixcontact.com/pc/products/2902990

Approvals



EAC

Approval ID: RU*DE*08.B.01187/19



UL Listed

Approval ID: FILE E 123528



cUL Listed

Approval ID: FILE E 123528



2902990

https://www.phoenixcontact.com/pc/products/2902990

Classifications

UNSPSC 21.0

ECLASS

ECLASS-11.0	27210992
ECLASS-12.0	27210992
ECLASS-13.0	27210992
ETIM	
ETIM 8.0	EC002498
UNSPSC	

39121000



2902990

https://www.phoenixcontact.com/pc/products/2902990

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com