

ECO-RAIL-2 POWER SUPPLY 1-PHASE,

IN: 90 ... 132 VAC / 173 ... 264 VAC OUT: 24V/20ADC


INPUT: 90...132 V AC/173...264 V AC

OUTPUT: 23...28 V DC

Current: 20 A

[Link to Product](#)**Illustration**

Product may differ from Image

**Input**

Input voltage	90...132 V AC/173...264 V AC
Input current	7.8 A (100 V AC); 4.0 A (200 V AC)
Inrush current after 1 ms	max. 40 A (230 V AC)
Frequency	50...60 Hz
Input fuse (internal)	12 A (T)

Output

Output voltage	24 V DC $\pm 1\%$; 23...28 V adjustable
LED display	LED (green) for output voltage
Output current	20 A (+40 °C); 16 A (+55 °C)
Mains failure bridging time	min. 15 ms (115 V AC); min. 20 ms (230 V AC)
Ripple	max. 50 mV eff/rms
Spikes	max. 100 mV ss/pp
Unit protection	short-circuit and overload protected
Parallel usage/serial usage	no/yes (max. 2 units)

General data

Standards	IEC 61010-2-201, EN 61204-3, EN 61000-3-2
Mounting method	DIN-rail mountable TH35 (EN 60715)
Temperature range	0...+40 °C, ...+55 °C derating (storage temperature -20...+85 °C)
Relative humidity	20...90%, no condensation
Protection	IP20
Efficiency	89% (115 V AC); 90% (230 V AC)

The information in this Product-PDF has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2023-07-12

Murrelektronik GmbH | Falkenstr. 3 | 71570 Oppenweiler | Fon +49 (71 91) 47-0 | Fax +49 (71 91) 47-491000 | shop@murrelektronik.com | shop.murrelektronik.com

Connection	Screw terminals
Dimensions H×W×D	124×105×124 mm
