

connection terminal plate, 3-pole (01199)



The picture may show a similar product.



Description

Part No.: **01199000**

CRITO[®] 60Classic

connection terminal plate, 3-pole

95 - 185 mm²

for busbars 20, 25, 30 x 5, 10 and section busbars

System

60Classic

Advantages of the product

Terminals with captive clamping screws

Conductor can be overlapped

Indication of nominal cross-section and tightening torque noted on the terminals.

Product group 07
Subgroup 48

pack size 1
EAN 4021267011994

catalog page 2020 : 3.5

ECLASS 6.1 27141146
ECLASS 7.1 27141146
ETIM 4.0 EC000001
ETIM 5.0 EC000001

Approvals

Standards

IEC 61439-1:2011
IEC 60999-1:1999
IEC 60999-2:2003

Approvals

DNV GL , EAC



EAC Type: TE-3P

CCC approval: no certification required

Technical data

Details IEC

Standards

IEC 61439-1:2011
IEC 60999-1:1999
IEC 60999-2:2003

Electrical data IEC

Rated current (IEC): 350 A
rated voltage (IEC) AC: 690 V

The insulation performance of the article depends on the installation conditions.

rated peak withstand current I_{pk} max.: 55.8 kA

Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

max. permitted voltage (IEC) AC: 1000 V
max. permitted voltage (IEC) DC: 1500 V
current capacity (IEC) max.: 460 A

Mechanical data

W x H x D: 135 x 200 x 118
weight: 132.2 kg/100
poles: 3-pole
for busbars: 20, 25, 30 x 5, 10 and section busbars

Terminal points

min. cross-section: 95 mm²
max. cross-section: 185 mm²

Suitable for aluminium cables.

When using aluminium cables, observe the maintenance instructions.

für Anwendungen nach IEC / EN :

Cu und Al 95 - 185 mm² Rundleiter mehrdrähtig und Sektorleiter mehrdrähtig
Cu auch feindrähtig, direkt geklemmt

for applications acc. to IEC / EN:

Cu or Al 95 - 185mm², round stranded or sector-shaped stranded cables
also fine stranded Cu cables (direct clamping)