# **Product datasheet**

Specification



comb busbar, Acti9, 3P+N balanced, 9 mm pitch, 48 modules, 80A

A9XPC748

#### Main

Range	Acti9	
product or component type	Comb busbar	
mounting mode	Horizontal	
Accessory / separate part categor	Connection accessory	
Lines description	3L + N	
Length in 18 mm modules	48	

## Complementary

Number of ways	16 ways N + 3 L (balanced)	
Poles configuration for 1 way	1 x 3P + N 1 x 3P 3 x 1P + N	
Connection pitch	9 mm between phase and neutral 18 mm between phases	
Connector type	Tooth	
Distance between way	54 mm	
Marking	N L1 N L2 N L3	
Insulation	Insulated	
device presentation	e presentation Cuttable	
e] rated operational current 80 A at 40 °C		
[Ue] rated operational voltage	230 V AC Ph/N 400 V AC Ph/Ph	
[Ui] rated insulation voltage	440 V AC conforming to IEC 61439-1	
[Uimp] rated impulse withstand voltage	4 kV	
Mounting location	Top on tunnel type terminals	
9 mm pitches	96	
Height	29 mm	
Width	862 mm	
Depth	26 mm	
net weight	579 g	
Colour	White (RAL 9003)	

Range compatibility	Acti 9 Acti9 C40	
	Acti 9 Acti9 C40 V	

Acti 9 Acti9 C40 Vigi Acti 9 Acti9 iDPN Acti 9 Acti9 iDPN Vigi Multi9 Multi9 N40 Vigi Acti9 Acti9 iC40 Acti9 Acti9 iCV40 Acti9 Vigi iCG40 Acti9 Acti9 iID40

## **Environment**

Standards	EN/IEC 60439-1
Fire resistance	960 °C ( 30 s ) conforming to IEC 60695-2-1
Pollution degree	3 conforming to EN/IEC 60439-1
IP degree of protection	IP20 with end-pieces and tooth covers

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 cm
Package 1 Width	3 cm
Package 1 Length	86.4 cm
Package 1 Weight	580 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	7 cm
Package 2 Width	9 cm
Package 2 Length	89.2 cm
Package 2 Weight	3.604 kg
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	45 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	256.16 kg



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>⊘</b>	Reach Free Of Svhc	
<b>⊘</b>	Toxic Heavy Metal Free	
<b>⊘</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations