

Panel Cutout 9.47 240.6 0 \bigcirc Ф 3.15 ±.010 2.76 ±.004 [80.0 ±0.2] [70.0 ±0.1] 6.49 [165.0] \emptyset 0.26 +.010 4.80 ±.010 0 [6.5 +0.2] [122.0 ±0.2] 5.83 ±.004 [148.0 ±0.1] Ø0.45∟ 0.20 [11.5∟ 5.5] 6.50 [165.0] Ø0.26 ±.004 $[6.5 \pm 0.1]$ ◉ 3.78 96.0 0 3.75 95.2 0 1.62 [41.1] Typical Cable Length: 6' Ш .39 [10.0]

NOTE:

- 1) REFER TO INSTALLATION INSTRUCTIONS TO ENSURE PROPER INSTALLATION.
- 2) ALWAYS FOLLOW YOUR LOCAL/FACILITY ELECTRICAL CODES AND PROCEDURES.
- 3) FOR DETAILED COMPONENT WIRING AND SPECIFICATIONS, REFER TO THE APPLICABLE DATA SHEETS.
- 4) COMPONENT LOCATIONS OUTLINED IN DRAWING ARE APPROXIMATE
- 5) FOR ACTUAL PRODUCT CONFORMITY, LISTINGS AND CERTIFICATIONS, REFER TO FINISHED PRODUCT FACEPLATE DRAWING, OR CONSULT FACTORY.

