



The module (Item No. 750-1689) has two independently switchable relay outputs (RO1 ... RO2) and is particularly suitable for applications that, e.g., individually electrically isolated Outputs are required, high loads must be switched or controlled with different voltage types (e.g., DC and AC voltage). The module supports operating voltages up to 250 VAC and 250 VDC.

The electrically isolated outputs can be freely combined with each other, so that Cat. 2 or Cat. 4 architectures up to SIL3 or PLe are possible. Details on possible wiring variants can be found in the product manual.

The relay outputs must be controlled via safe digital outputs (e.g., the outputs of the 75x-667/000-004, 750-1665/000-004 module), in which case an unsafe enable of the relay outputs must also be provided via the process image.

The status of the safe relay outputs and the temperature for each relay are detected and transmitted to the controller via the non-safe process image, where they must be evaluated as diagnostics.

The field and system levels are electrically isolated from each other.

The individual safe modules can be arranged in any configuration in the fieldbus node.

The module (Item No. 750-1689) was evaluated by UL in accordance with UL/CSA 61010-1, UL/CSA 61010-2-201 and UL 121201, CSA-C22.2 No. 213. The functional safety assessment according to the above standards was carried out by TÜV Rheinland.

Technical data	
Indicators	LED (A/B) green: Status RO1 ... RO2
Number of F I/O modules per node (fieldbus coupler/controller)	See information in the manual about the respective fieldbus coupler/controller
Supply voltage (system)	5 VDC; via data contacts
Current consumption (5 V system supply)	15 mA

Relay control signals	
Signal type	Digital
Cable length (max.)	3 m
Reverse voltage protection	Yes
Input voltage (max.)	24 VDC (-25 ... +30 %)
Input current (max.)	15 mA (Control current per channel max.)
Test pulse duration (max.)	1 ms

Relay outputs	
Number of digital outputs	2
Output circuit design	2 make contacts; relay
Signal type	Digital
Actuator connection	2 x (2-wire)
Output characteristic	potential-free
Switching voltage (max.)	250 VAC; 250 VDC
Switching power	AC: 0.1 VA ... 1500 VA; DC: 200 W; see load limit curve



Relay outputs	
Output current (per channel)	6 A at 250 VAC (resistive load); 6 A at 31,2 VDC (resistive load); 3 A at 60 VDC (resistive load); 0,8 A at 110 VDC (resistive load); 0,3 A at 250 VDC (resistive load); 2 A at 31,2 VDC (Pilot Duty); UL: R300 Pilot Duty according to UL508; UL: B300 Pilot Duty according to UL508
Switching capacity	AC-15: 3 A / 250 VAC; DC-13: 2 A / 31.2 VDC
Output current (module)	12 A
Limitation of the inductive switch-off voltage	nein
Drop-out time (typ.)	50 ms
Pull-in time (max.)	10 ms
Short-circuit withstand capacity	1 kA / 250 VAC IEC/EN 60947-5-1
Fuse	Each channel requires its own external fuse; max. 10 A slow; min. approved for the switching voltage used
Switching frequency (max.)	1 Hz; Resistive load
Switching frequency (max.) (2)	0.1 Hz; Inductive load
Contact load	2 mA (min.); 10 mA after a single overflow of 300 mA load current or a switching power of 12 W or 12 VA
Diagnostics	Relay status in the process image via force-guided contact
Electrical switching operations (min.) (at max. resistive load)	1 x 10 ⁶ switching operations
Mechanical switching operations (min.) (at max. resistive load)	40 x 10 ⁶ switching operations
Contact material	AgNi + 5µm Au
B10d values (resistive load)	Resistive load (at 230 VAC); 6 A: 600,000; 3 A: 6,000,000; 2 A: 10,000,000; 1 A: 12,000,000 switching cycles Resistive load (at 24 VDC); 6 A: 4,000,000; 3 A: 10,000,000; 2 A: 14,000,000; 1 A: 20,000,000 switching cycles
B10d (15 AAC)	AC-15 (at 230 VAC); 3 A: 6,000,000; 2 A: 10,000,000; 1 A: 12,000,000; 0.5 A: 20,000,000 switching cycles
B10d (DC 13)	DC-13 (at 24 VDC); 2 A: 4,000,000; 1 A: 8,000,000; 0.5 A: 15,000,000 switching cycles

Safety and protection	
System voltage	≤ 250 V
Note on system voltage	The system voltage is derived from the line-to-neutral voltage for common MAINS supply systems.

Insulation coordination	
Overvoltage category	per EN 60664-1: III; per EN/UL 61010-2-201: II
Insulation type	Relay: Reinforced insulation; Channel/channel: Reinforced insulation; Control/system: Functional insulation

Test voltage	
Test voltage	Test voltage (relay): 3.51 kVAC, 50/60 Hz, 1 min.; Test voltage (control/system): 500 VDC, 1 min.
Rated impulse withstand voltage	6 kV (relay)



Functional Safety	
Achievable safety classes	Two-Channel Cat. 4/PL e per EN ISO 13849-1; SIL 3 per IEC 61508 / EN 62061; Single-Channel Cat. 2/PL d per EN ISO 13849-1; SIL 2 per IEC 61508 / EN 62061
Safety standards	IEC 61508-1 ... -7; EN ISO 13849-1; EN 62061; DIN EN 61810-1, DIN EN 61810-3
Service life	20 years

Connection data	
Connection technology: inputs/outputs	8 x Push-in CAGE CLAMP® (outputs)
Connectable conductor materials	Copper
Connection type	Output
Solid conductor	0.14 ... 1.5 mm² / 28 ... 16 AWG
Fine-stranded conductor; with insulated ferrule	0.25 ... 0.75 mm²
Fine-stranded conductor; with uninsulated ferrule	0.25 ... 1.5 mm²
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches

Physical data	
Width	24 mm / 0.944 inches
Height	100 mm / 3.937 inches
Depth	69.8 mm / 2.748 inches
Depth from upper-edge of DIN-rail	62.6 mm / 2.465 inches

Mechanical data	
Mounting type	DIN-35 rail
Pluggable connector	fixed

Material data	
Housing material	Polycarbonate; polyamide 6.6
Fire load	1.4 MJ
Weight	93.5 g

Environmental requirements	
Ambient temperature (operation)	0 ... +55 °C
Ambient temperature (storage)	-40 ... +85 °C
Protection type	IP20
Pollution degree	2
Protection class	II
Operating altitude	0 ... 2000 m / 0 ... 6562 ft
Mounting position	Horizontal left, horizontal right, horizontal top, vertical top and vertical bottom
Relative humidity (without condensation)	95 %
Vibration resistance	4g per IEC 60068-2-6
Shock resistance	15g per IEC 60068-2-27
EMC immunity to interference	Per EN 61000-6-2; marine applications; EN 61000-6-7 (FS); EN 61326-3-1:2017
EMC emission of interference	per EN 61000-6-4, marine applications, EN 61000-6-3
Exposure to pollutants	per IEC 60068-2-42 and IEC 60068-2-43
Permissible H ₂ S contaminant concentration at a relative humidity 75 %	10 ppm
Permissible SO ₂ contaminant concentration at a relative humidity 75 %	25 ppm



Conformity marking	CE; UKCA
EU Directive	EU Machinery Directive: 2006/42/EC; EU Low Voltage Directive (LVD): 2014/35/EU; EU EMC Directive: 2014/30/EU

Commercial data	
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4066966764451
Customs tariff number	85371098990

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	-	E175199

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 750-1689 

1 Compatible Products

1.1 Optional Accessories

1.1.1 DIN-rail

1.1.1.1 Mounting accessories



Item No.: 210-196
Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored



Item No.: 210-198
Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; copper-colored



Item No.: 210-508
Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; galvanized; similar to EN 60715; silver-colored



Item No.: 210-197
Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715; silver-colored



Item No.: 210-506
Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; galvanized; similar to EN 60715; silver-colored



Item No.: 210-114
Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored



Item No.: 210-118
Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored



Item No.: 210-115
Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm; silver-colored



1.1.1.1 Mounting accessories



Item No.: 210-112
Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm; silver-colored



Item No.: 210-504
Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; galvanized; according to EN 60715; silver-colored



Item No.: 210-113
Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored



Item No.: 210-505
Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; galvanized; according to EN 60715; silver-colored

1.1.2 Marking

1.1.2.1 Group marker carrier



Item No.: 750-107
Group marker carrier

1.1.2.2 Marker



Item No.: 2009-145/000-006
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue



Item No.: 2009-145/000-007
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray



Item No.: 2009-145/000-023
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green



Item No.: 2009-145/000-012
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange



Item No.: 2009-145/000-005
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; red



Item No.: 2009-145/000-024
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet



Item No.: 2009-145
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white



Item No.: 2009-145/000-002
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow



Item No.: 248-501/000-006
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; blue



Item No.: 248-501/000-007
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; gray



Item No.: 248-501/000-023
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; green



Item No.: 248-501/000-017
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; light green



Item No.: 248-501/000-012
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; orange



Item No.: 248-501/000-005
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; red



Item No.: 248-501/000-024
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; violet



Item No.: 248-501
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white



Item No.: 248-501/000-002
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; yellow

1.1.2.3 Marker carrier



Item No.: 750-103
Group marker carrier



1.1.3 Shield termination

1.1.3.1 Shield clamping saddles

 Item No.: 790-108 Shield clamping saddle; 11 mm wide; diameter of compatible conductor; 3 ... 8 mm	 Item No.: 790-208 Shield clamping saddle; 12.4 mm wide; 3 ... 8 mm	 Item No.: 790-116 Shield clamping saddle; 19 mm wide; diameter of compatible conductor; 7 ... 16 mm	 Item No.: 790-216 Shield clamping saddle; 21.8 mm wide; 6 ... 16 mm
 Item No.: 790-124 Shield clamping saddle; 27 mm wide; diameter of compatible conductor; 6 ... 24 mm	 Item No.: 790-220 Shield clamping saddle; 30 mm wide; 6 ... 20 mm	 Item No.: 790-140 Shield clamping saddle; diameter of compatible conductor	

1.1.4 Supply module

1.1.4.1 Supply module

 Item No.: 750-612 Power Supply; 0 ... 230 V AC/DC	 Item No.: 750-602 Power Supply; 24 VDC	 Item No.: 750-601 Power Supply; 24 VDC; fuse holder	 Item No.: 750-610 Power Supply; 24 VDC; fuse holder; Diagnostics
--	---	---	---

1.1.5 System enclosure

1.1.5.1 System enclosure

 Item No.: 850-825 IP65 enclosure; Aluminium (RAL 7032); WxHxD (160x100x160 mm); 9 x M12, 4 x M20	 Item No.: 850-826 IP65 enclosure; Aluminium (RAL 7032); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip	 Item No.: 850-827 IP65 enclosure; Aluminium (RAL 7032); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip	 Item No.: 850-828 IP65 enclosure; Aluminium (RAL 7032); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip
 Item No.: 850-826/002-000 IP65 enclosure; Aluminium (RAL 7035); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip	 Item No.: 850-827/002-000 IP65 enclosure; Aluminium (RAL 7035); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip	 Item No.: 850-828/002-000 IP65 enclosure; Aluminium (RAL 7035); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip	 Item No.: 850-834 IP65 enclosure; Polyester (RAL 7032); WxHxD (164x100x164 mm); 9 x M12, 4 x M20
 Item No.: 850-835 IP65 enclosure; Polyester (RAL 7032); WxHxD (244x100x164 mm); 4 x M20, 4 x M16, 14 x M12 cable grip	 Item No.: 850-836 IP65 enclosure; Polyester (RAL 7032); WxHxD (324x100x164 mm); 4 x M20, 8 x M16, 17 x M12 cable grip	 Item No.: 850-814/002-000 IP65 enclosure; Sheet steel (RAL 7035); WxHxD (200x120x200 mm); without flange plate	 Item No.: 850-815/002-000 IP65 enclosure; Sheet steel (RAL 7035); WxHxD (300x120x200 mm); without flange plate
 Item No.: 850-816/002-000 IP65 enclosure; Sheet steel (RAL 7035); WxHxD (400x120x200 mm); without flange plate	 Item No.: 850-817/002-000 IP65 enclosure; Sheet steel (RAL 7035); WxHxD (600x120x200 mm); without flange plate		

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com