

**HDC-KIT-HA 04.401 P****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

HDC kits are standardized kits for assembling complete plug-in connectors.

The HDC kits normally consist of a male insert, a female insert, a plug housing, a bulkhead housing and a cable gland.

Weidmüller offers a range of standard connector combinations with metric or PG cable entry threads.

The PUSH IN connection is a direct-insert method of connection. The preprocessed wire can be inserted directly into the wire connection without the need for any tools.

PUSH IN technology

**General ordering data**

|            |   |
|------------|---|
| Version    | RockStar® , HA, Size: 1, PUSH IN, 230 V, 10 A, Plastic, PG 11 |
| Order No.  | <a href="#">3123950000</a>                                    |
| Type       | HDC-KIT-HA 04.401 P   |
| GTIN (EAN) | 4099987272582   |
| Qty.       | 1 ST  |

## HDC-KIT-HA 04.401 P

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |      |
|------------|------|
| Net weight | 99 g |
|------------|------|

## Temperatures

|                   |                   |
|-------------------|-------------------|
| Limit temperature | -40 °C ... 100 °C |
|-------------------|-------------------|

## General data

|                       |                             |                |                |
|-----------------------|-----------------------------|----------------|----------------|
| Housing main material | Plastic                     | Surface finish | Powder coating |
| Protection degree     | IP65 (in plugged condition) | Series         | HA             |

## Version

|                       |          |                              |   |
|-----------------------|----------|------------------------------|---|
| Size of cable entries | PG 11    | Number of cable entry on top | 1 |
| Type of connection    | PUSH IN  | Size                         | 1 |
| Colour (RAL)          | RAL 7035 | BG                           | 1 |

## General data

|                              |         |                              |                    |
|------------------------------|---------|------------------------------|--------------------|
| Number of poles              | 4       | Connection type PE           | PUSH IN connection |
| Size                         | 1       | Cable glands                 | PG 11              |
| Material                     | Plastic | Series                       | HA                 |
| Rated voltage (DIN EN 61984) | 230 V   | Rated current (DIN EN 61984) | 10 A               |
| BG                           | 1       |                              |                    |

## Version

|                               |                     |                               |                     |
|-------------------------------|---------------------|-------------------------------|---------------------|
| Type of connection            | PUSH IN             | Size                          | 1                   |
| Conductor cross-section, max. | 2.5 mm <sup>2</sup> | Conductor cross-section, min. | 0.5 mm <sup>2</sup> |
| Surface finish                | Powder coating      | Max. torque for main contact  | 0.55 Nm             |
| Material                      | Plastic             | Min. torque for main contact  | 0.5 Nm              |
| BG                            | 1                   |                               |                     |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002943    | ETIM 7.0    | EC002943    |
| ETIM 8.0    | EC002943    | ETIM 9.0    | EC002943    |
| ETIM 10.0   | EC002943    | ECLASS 9.0  | 27-44-02-92 |
| ECLASS 9.1  | 27-44-01-90 | ECLASS 10.0 | 27-44-02-92 |
| ECLASS 11.0 | 27-44-02-92 | ECLASS 12.0 | 27-44-02-92 |
| ECLASS 13.0 | 27-44-02-92 | ECLASS 14.0 | 27-44-02-92 |
| ECLASS 15.0 | 27-44-02-92 |             |             |