



Data Sheet | Item Number: 857-531

Threshold value switches; Analog values; 1 changeover contact; Digital output;
Configuration via software; Supply voltage: 24 VDC; 6 mm module width; 2,50 mm²

<https://www.wago.com/857-531>





857-531
Push/Side Switch Operation


Switching Behavior	Number of Switching Points	Values for Switching Points	Switching Point 1, Relay	Switching Point 2, Relay	Configuration			
					Press for 1 sec.	Yellow LED flashes	Red LED flashes briefly	No flashing LED
1	1	S1	,ON'	-				
2	1	S1	,ON''	-				
3	2	S1 + S2	,ON'	,ON'				
4	2	S1 + S2	,ON'	,ON''				
5	2	S1 + S2	,ON''	,ON'				
6	2	S1 + S2	,ON''	,ON''				
Exit parameterization mode without entering a value	-	-	-	-				

DIP-Switch S1				
Input Signal Limits ±0.25 V; ±0.5 mA				Hysteresis
1	2	3	4	5
				±10 V
	•			0 ... 10 V
	•			2 ... 10 V
	•			0 ... 5 V
		•		1 ... 5 V
	•			±5 V
	•	•		0 ... 15 V
	•	•	•	0 ... 30 V
•				±20 mA
•	•			0 ... 20 mA
•	•			4 ... 20 mA
•	•			0 ... 10 mA
		•		2 ... 10 mA
•	•			±10 mA


DIP Switch S1				
Configurable Rise/Fall Delay Time in sec.				Digital Output DO Signaling
6	7	8	9	10
				DO NOT active
•	•		•	GND → U _i (switching)
			•	U _i → GND (switching)
•	•			
		•		
•	•			
		•		
•	•			
		•		



DC load limit curve



Current-carrying capacity curve



Short description:

This threshold value switch for analog signals monitors standard analog signals and reports signals exceeding a preset threshold.

Configurable digital switching output:

GND switching: The digital output (DO) is switched to "GND" for all input values that are smaller than the lower switching threshold or greater than the upper switching threshold.

U_s switching: For all input values that are smaller than the lower switching threshold or greater than the upper switching threshold, the digital output (DO) adopts the value of the supply voltage.

The preset switching thresholds are 0% and 100% ($\pm 0.25\text{ V}$ / $\pm 0.5\text{ mA}$) of the input measurement range. The switching thresholds can be adjusted via the interface configuration software.

Features:

- PC configuration interface
- Changeover relay output
- Calibrated measurement range switching
- Threshold value configuration via DIP switch and teach-in function via push/slide switch
- 3-way electrical isolation with 3 kV test voltage



Notes	
Safety Information	The input and digital output must be safely isolated from hazardous live parts!
Note	Use shielded signal cables! Only use shielded signal cables for analog input and output signals. This ensures the device maintains its specified accuracy and immunity to interference, even when external disturbances affect the signal cable. Additional setting options via the WAGO Interface Configuration Software

Technical data	
Configuration	
Configuration options	DIP switch WAGO Interface Configuration Software Push/slide switch
Input	
Input signal type	Voltage Current
Input signal (voltage)	±10 V 0 ... 30 V
Input signal (current)	±20 mA
Input resistance (current input)	≤ 200 Ω
Input resistance (voltage input)	≥ 100 kΩ
Input current (max.)	22 mA
Input voltage (max.)	31 V

Output (digital)	
Switching voltage (DO) max.	Supply voltage applied
Continuous current (DO) max.	100 mA (no internal restriction)
Number of switching thresholds (DO)	2 (adjustable)

Output (relay)	
Number of changeover/switchover contacts	1
Switching Voltage, Max.	250 VAC
Switching power (resistive) max.	AC 1500 VA; DC (see load limit curve)
Drop-out time (typ.)	4 ms
Number of switching thresholds (relay)	1 or 2 (adjustable)
Configurable rise/fall delay time (relay)	0 ... 30 s (via software)
Continuous current (max.)	6 A

Signal processing	
Hysteresis	Adjustable via DIP switch or software (valid for relays and DO)
Step response (typ.)	16 ms

Measurement error	
Transmission error (typ.)	≤ 0.1 % of upper-range value
Temperature coefficient	≤ 0.01 %/K

Power supply	
Power supply type	24 VDC (SELV)
Nominal supply voltage U _S	24 VDC
Supply voltage range	±30 %
Current consumption at nominal supply voltage	≤ 25 mA (+ I _{DO})

Safety and protection	
Rated Voltage	300 V
Protection type	IP20
Test voltage	
Test voltage (input/relay output/supply)	3 kVAC; 50 Hz; 1 min



Insulation coordination	
Overvoltage category	II
Pollution degree	2
Insulation type (input/supply)	Reinforced insulation (safe isolation)
Insulation type (relay)	Reinforced insulation (safe isolation)
Insulation type (adjacent devices)	Reinforced insulation (safe isolation)

Connection data	
Connection technology	Push-in CAGE CLAMP®
Solid conductor	0.08 ... 2.5 mm² / 28 ... 14 AWG
Fine-stranded conductor	0.34 ... 2.5 mm² / 22 ... 14 AWG
Strip length	9 ... 10 mm / 0.35 ... 0.39 inches

Physical data	
Width	6 mm / 0.236 inches
Height	94 mm / 3.701 inches
Depth from upper-edge of DIN-rail	97.8 mm / 3.85 inches

Mechanical data	
Mounting type	DIN-35 rail

Material data	
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.013 MJ
Weight	38.6 g

Environmental requirements	
Ambient temperature (operation)	-25 ... +70 °C
Ambient temperature (storage)	-40 ... +85 °C
Temperature range of connection cable	≥ (T _{ambient} + 35 K)
Relative humidity	5 ... 85 % (no condensation permissible)
Operating altitude (max.)	2000 m

Standards and specifications	
Conformity marking	CE
EMC immunity to interference	EN 61000-6-2; EN 61131-2; EN 61326-1; EN 50121-3-2
EMC emission of interference	EN 61000-6-4; EN 61131-2; EN 61326-1; EN 50121-3-2
Standards/specifications	EN 61373



Commercial data	
Product Group	6 (INTERFACE ELECTRONIC)
PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	DE
GTIN	4066966662375
Customs tariff number	90303370000

Product Classification	
UNSPSC	39122331
eCl@ss 10.0	27-21-01-20
eCl@ss 9.0	27-21-01-20
ETIM 9.0	EC002653
ETIM 8.0	EC002653
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
CAS-No.	1303-86-2 1317-36-8 7439-92-1 75980-60-8 79-94-7 80-05-7
REACH Candidate List Substance	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol 4,4'-isopropylidenediphenol Diboron trioxide Lead Lead monoxide Phosphine oxide, diphenyl(2,4,6-trimethylbenzoyl)-
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c) 7(a) 7(c)-I 7(c)-II
SCIP notification number (Bulgaria)	70c9867b-9228-49b1-8871-0ff4880135a1
SCIP notification number (Czech Republic)	475d917f-e72d-4462-a17f-b1550a3b1393

Approvals / Certificates	
General approvals	Declarations of conformity and manufacturer's declarations

 		
Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03078
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081
UL Underwriters Laboratories Inc. (ORDINARY LOCATI- ONS)	UL 508	E175199 Sec.4

Approval	Standard	Certificate Name
EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-



Approvals for marine applications



Approval	Standard	Certificate Name
BV Bureau Veritas S.A.	Rules for class. of Steel Ships	40179_B0
DNV DNV Germany GmbH	DNV-CG-0339,Aug.2021	TAA00001D1

Approvals for hazardous areas



Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc. (HAZARDOUS LOCATIONS)	ANSI/ISA 12.12.01	E198726

Downloads

Environmental Product Compliance

Compliance Search
Environmental Product Compliance 857-531

Documentation

Manual
WAGO Threshold Value Switches

Bid Text			
857-531	20.02.2019	docx 17.50 KB	
857-531	19.02.2019	xml 6.25 KB	

Instruction Leaflet			
Messumformer und Trennverstärker	V 2.2.2 28.03.2023	pdf 3367.84 KB	

CAD/CAE-Data

CAD data
2D/3D Models 857-531

CAE data
EPLAN Data Portal 857-531
WSCAD Universe 857-531
ZUKEN Portal 857-531



1 Compatible Products			
1.1 Optional Accessories			
1.1.1 Cables and connectors			
1.1.1.1 Communication cable			
			
Item No.: 750-923/000-001 Configuration cable; USB connector; Length: 5 m			
1.1.2 Communication			
1.1.2.1 Bluetooth			
			
Item No.: 750-921 Bluetooth® Adapter			
1.1.2.2 Communication cable			
			
Item No.: 750-923 Configuration cable; USB connector; Length: 2.5 m			
1.1.3 Interface module			
1.1.3.1 Interface adapters			
			
Item No.: 857-980 Interface adapter; 16-pole; analog			
1.1.4 Jumper			
1.1.4.1 Jumper			
			
Item No.: 281-482 Jumper; 2-way; insulated; gray	Item No.: 859-410/000-006 Jumper; for jumper slot; 10-way; insula- ted; blue	Item No.: 859-410 Jumper; for jumper slot; 10-way; insula- ted; light gray	Item No.: 859-410/000-005 Jumper; for jumper slot; 10-way; insula- ted; red
			
Item No.: 859-410/000-029 Jumper; for jumper slot; 10-way; insula- ted; yellow	Item No.: 859-402/000-006 Jumper; for jumper slot; 2-way; insulated; blue	Item No.: 859-402 Jumper; for jumper slot; 2-way; insulated; light gray	Item No.: 859-402/000-005 Jumper; for jumper slot; 2-way; insulated; red
			
Item No.: 859-402/000-029 Jumper; for jumper slot; 2-way; insulated; yellow	Item No.: 859-403/000-006 Jumper; for jumper slot; 3-way; insulated; blue	Item No.: 859-403 Jumper; for jumper slot; 3-way; insulated; light gray	Item No.: 859-403/000-005 Jumper; for jumper slot; 3-way; insulated; red



1.1.4.1 Jumper



Item No.: 859-403/000-029
Jumper; for jumper slot; 3-way; insulated; yellow



Item No.: 859-404/000-006
Jumper; for jumper slot; 4-way; insulated; blue



Item No.: 859-404
Jumper; for jumper slot; 4-way; insulated; light gray



Item No.: 859-404/000-005
Jumper; for jumper slot; 4-way; insulated; red



Item No.: 859-404/000-029
Jumper; for jumper slot; 4-way; insulated; yellow



Item No.: 859-405/000-006
Jumper; for jumper slot; 5-way; insulated; blue



Item No.: 859-405
Jumper; for jumper slot; 5-way; insulated; light gray



Item No.: 859-405/000-005
Jumper; for jumper slot; 5-way; insulated; red



Item No.: 859-405/000-029
Jumper; for jumper slot; 5-way; insulated; yellow



Item No.: 859-406/000-006
Jumper; for jumper slot; 6-way; insulated; blue



Item No.: 859-406
Jumper; for jumper slot; 6-way; insulated; light gray



Item No.: 859-406/000-005
Jumper; for jumper slot; 6-way; insulated; red



Item No.: 859-406/000-029
Jumper; for jumper slot; 6-way; insulated; yellow



Item No.: 859-407/000-006
Jumper; for jumper slot; 7-way; insulated; blue



Item No.: 859-407
Jumper; for jumper slot; 7-way; insulated; light gray



Item No.: 859-407/000-005
Jumper; for jumper slot; 7-way; insulated; red



Item No.: 859-407/000-029
Jumper; for jumper slot; 7-way; insulated; yellow



Item No.: 859-408/000-006
Jumper; for jumper slot; 8-way; insulated; blue



Item No.: 859-408
Jumper; for jumper slot; 8-way; insulated; light gray



Item No.: 859-408/000-005
Jumper; for jumper slot; 8-way; insulated; red



Item No.: 859-408/000-029
Jumper; for jumper slot; 8-way; insulated; yellow



Item No.: 859-409/000-006
Jumper; for jumper slot; 9-way; insulated; blue



Item No.: 859-409
Jumper; for jumper slot; 9-way; insulated; light gray



Item No.: 859-409/000-005
Jumper; for jumper slot; 9-way; insulated; red



Item No.: 859-409/000-029
Jumper; for jumper slot; 9-way; insulated; yellow

1.1.5 Marking

1.1.5.1 Marker



Item No.: 793-5501
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; white



Item No.: 793-502
WMB marking card; as card; MARKED; 1 ... 10 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-566
WMB marking card; as card; MARKED; 1 ... 50 (2x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-503
WMB marking card; as card; MARKED; 11 ... 20 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-504
WMB marking card; as card; MARKED; 21 ... 30 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-505
WMB marking card; as card; MARKED; 31 ... 40 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-506
WMB marking card; as card; MARKED; 41 ... 50 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-501
WMB marking card; as card; not stretchable; plain; snap-on type; white



Item No.: 2009-115
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

1.1.5.2 Marking strip



Item No.: 2009-110
Marking strips; for Smart Printer; on reel;
not stretchable; plain; snap-on type; white

1.1.6 Power supply

1.1.6.1 Power Supply



Item No.: 787-2852
Switched-mode power supply; 1-phase;
24 VDC output voltage; 1 A output current

1.1.7 Relay module

1.1.7.1 Relay module



Item No.: 857-304
Relay module; Nominal input voltage: 24
VDC; 1 changeover contact; Limiting con-
tinuous current: 6 A; Yellow status indica-
tor; Module width: 6 mm; gray

1.1.8 Screwless end stop

1.1.8.1 Mounting accessories



Item No.: 249-117
Screwless end stop; 10 mm wide; for DIN-
rail 35 x 15 and 35 x 7.5; gray



Item No.: 249-197
Screwless end stop; 14 mm wide; for DIN-
rail 35 x 15 and 35 x 7.5; gray



Item No.: 249-116
Screwless end stop; 6 mm wide; for DIN-
rail 35 x 15 and 35 x 7.5; gray

1.1.9 Terminal blocks

1.1.9.1 Supply module



Item No.: 857-979
Supply and through module

1.1.9.2 Through terminal block



Item No.: 857-979
Supply and through module

1.1.10 Tool


1.1.10.1 Operating tool




Item No.: 210-720
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured

Installation Notes

Configuring



Configuration via DIP switch




Configuration via WAGO Interface Configuration Software



Configuration via push/slide switch

Commoning



Commoning, not discrete wiring – Same outline allows use of a single in-line, push-in jumper.