

PSSu E F 2DI 60-R

315201



PSSu, electronic module, failsafe, digital inputs and outputs, 2 inputs 60 V, for railway applications.

Technical details

General data

Approval:	CE, UKCA, cULus Listed, EAC (Eurasian), TÜV
Application range:	Failsafe

Technical data

Inputs

DC voltage at input:	24 - 72 V
Type of input voltage U1:	DC
Potential isolation inputs:	yes

Environmental data

App. site standard1 railway:	EN 50125-3
App. site to standard1 railway:	Track area (1m - 3m)
App. site standard2 railway:	EN 61373
App. site to standard2 railway:	Category 1, Class A + B
Climatic suitability to ...:	EN 50125-1, EN 60068-2-2, EN 60068-2-1, EN 50155, EN 60068-2-14, EN 50125-3
Ambient temperature standard:	EN 50155
Ambient temperature:	-40 - 70 °C
Standard 2 for ambient temp.:	EN 50125-1
Ambient temp. to standard 2:	-40 ... +70 °C
Standard 3 for ambient temp.:	EN 50125-3
Ambient temp. to standard 3:	-40 ... +70 °C

Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
Condensation permitted?:	Briefly
Perm. operating height ASL:	2000 m
EMC to standard ...:	EN 61000-4-4, EN 61000-6-2, EN 61000-4-5, EN 61000-4-6, EN 61000-6-4, EN 61000-4-2, EN 61000-4-3
Vibration to standard ...:	EN 50125-3
Broad band noise to:	EN 61373
Standard1 b/band noise, rail:	EN 61373
Freq. broadband noise, rail:	5 ... 150 Hz
Accel. broadband noise, rail:	0.79 g RMS
Acc. shock to standard1:	2g
Acc. shock to standard2:	5g
Clearance & creepage dist. to:	EN 50124-1
Overvoltage category:	OV2
Pollution degree clear.&creep.:	PD2
Protection type standard:	EN 60529
Protection type, housing:	IP20
Mechanical data	
Housing material lower section:	PC
Housing material front plate:	PC
Housing material code:	PA
Terminal style:	plug-in
Height dimension:	76 mm
Width dimension:	12.6 mm
Depth dimension:	60.2 mm
Net weight:	45 g
Gross weight:	45 g

Name of coding element:	N
Colour of coding element:	Yellow
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACH compliance:	Contains no SVHC substances
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27242604
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000024
ETIM Reference Feature:	EC001599
UNSPSC 25:	39122331
GTIN:	4046548067781
Volume:	0.049 dm3
Harmonized System Code:	85389091
Type of tariff number:	TARIC
Use of customs tariff number:	Ausfuhr, Einfuhr
Quantity per packaging unit:	1

Obligatory accessories



314600

PSSu BP 1/8 S-T



314601

PSSu BP 1/8 C-T



314618

PSSu BP 1/12 S-T

314619

PSSu BP 1/12 C-T



314622

PSSu BP-C1 1/12 S-T



314623

PSSu BP-C1 1/12 C-T

Optional accessories



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)



314902

PSSu A EC-T