

PSEN op3.3 Reflex NO/NC M12

630830



Reflected light sensor with N/O / N/C outputs for use as a mutingsensor, supply voltage 24 V, connector M12, 4-pin. Please note that a reflector (630323) must be ordered separately.

Technical details

General data

Approval:	CE, cULus Listed
Operating range (m):	0 - 9 m

Technical data

Electrical data

Supply voltage (V):	10 - 30 V
---------------------	-----------

Optical data

Used wavelength range:	640 nm
------------------------	--------

Environmental data

Ambient temperature:	-10 - 55 °C
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	30g
Protection type, housing:	IP67

Times

Reaction time:	0.5 - 0.5 ms
----------------	--------------

Mechanical data

Housing material:	ABS
Height dimension:	50 mm
Width dimension:	66 mm
Depth dimension:	18 mm

Net weight:	30 g
Gross weight:	78 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACH compliance:	Contains no SVHC substances
WEEE classification (08/2018):	0 not relevant
Commercial data	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27272792
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC003015
UNSPSC 25:	46171620
GTIN:	4046548082074
Volume:	0.614 dm3
Harmonized System Code:	90319000
Type of tariff number:	TARIC
Use of customs tariff number:	Ausfuhr, Einfuhr
Quantity per packaging unit:	1