

PNOZ m B0

772100



Configurable safe small controllers PNOZmulti 2, base unit, expandable, 20 safe digital inputs, 4 safe semiconductor outputs.

Technical details

General data

Approval:	CE, UKCA, cULus Listed, KOSHA, TÜV, EAC (Eurasian)
Application range:	Failsafe

Technical data

Electrical data

Purpose of U1:	System supply
Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	DC
Device circuit breaker U1:	6 A, automatic, Char.B
Purpose of U2:	Supply of SC outputs
Supply voltage U2:	24 - 24 V
Type of supply voltage U2:	DC
Potential isolation U2:	Yes
Permitted loads:	Resistive, Inductive, Capacitive

Configurable inputs/outputs

Number of configurable I/Os:	8
Potential isolation of IO:	No
Short circ. prot. n/safe S/C O:	Yes
Voltage at 1 n/safe S/C O:	UB - 2 V at 0.1 A

Inputs

U input to EN 61131-2 Type 1:	24 V DC
Potential isolation input:	No
Semiconductor outputs	
Potential isolation of S/C O:	Yes
S/C output short circuit proof:	Yes
Test clock outputs	
Number of test pulse outputs:	4
Environmental data	
Ambient temperature standard:	EN 60068-2-14
Ambient temperature:	0 - 60 °C
Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-30, EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
Condensation permitted?:	Not permitted
Perm. operating height ASL:	2000 m
EMC to standard ...:	EN 61131-2
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	15g
Clearance & creepage dist. to:	EN 61131-2
Overvoltage category:	II
Pollution degree clear.&creep.:	2
Protection type standard:	EN 60529
Protection type, housing:	IP20
Potential separation	
Potential isolation 1 between:	SC output and system voltage
Type of potential isolation 1:	Basic insulation
Mechanical data	
Mounting position:	horizontal on top hat rail
Housing material lower section:	PC

Housing material front plate:	PC
Housing material upper part:	PC
Connection terminal:	Spring-loaded terminal, Screw terminal
Terminal style:	plug-in
Flex. cond. c/s AWG info:	24 - 12 AWG
Height dimension:	101.4 mm
Width dimension:	45 mm
Depth dimension:	120 mm
Net weight:	235 g
Gross weight:	250 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	7a, 7c I
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead, Lead oxide
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1, 1317-36-8
SCIP entry available:	yes
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27242207
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000024
ETIM Reference Feature:	EC000236
UNSPSC 25:	39122331
GTIN:	4046548059137

Volume:	0.648 dm3
Harmonized System Code:	85371091
Type of tariff number:	TARIC
Use of customs tariff number:	Ausfuhr, Einfuhr
Quantity per packaging unit:	1

Obligatory accessories



750008

PNOZ s Set1screw terminals 45mm



751008

PNOZ s Set1spring loaded terminals 45mm



779201

PNOZmulti Chipcard 1 piece 8kb



779211

Chipcard 1 piece 32kB

Optional accessories



312992

PSSu A USB-CAB03




312993

PSSu A USB-CAB05




773010K

User Licence for PNOZmulti Config




773010U

Basic Upgr Licence for PNOZmulti Config




773011B

Basic Licence for PNOZmulti Service




773011K

User Licence for PNOZmulti Service



773011U

Basic Upgr Licence for PNOZmulti Service



773011V

User Upgr Licence for PNOZmulti Service



779200

PNOZmulti Chipcard Set 10 piece 8KB



779212

PNOZmulti Chipcard Set 10 pieces 32kB



779230

PNOZ Chip Card Reader



779240

PNOZmulti Chipcard Holder (Sparepart)



779250

PNOZmulti Seal 12 pieces



779260

PNOZ mm0.xp connector left (10 pcs)



779261

PNOZ mm0.xp terminator left (10 pcs.)