

PDP67 F 4 code VA

773613



Decentralised passive distributor for connection of PSENcode, PSENslock and PSENini to a Pilz control system, max. 4 sensors, protection type IP67, stainless steel connections.

Technical details

General data

Approval: CE, UKCA, cULus Listed, KOSHA

Technical data

Electrical data

Supply voltage (V): 24 - 24 V

Type of supply voltage U1: DC

Environmental data

Climatic suitability to ...: EN 60068-2-2, EN 60068-2-1, EN 60068-2-14

Ambient temperature standard: EN 60068-2-14

Ambient temperature: -40 - 60 °C

Storage temperature standard: EN 60068-2-1/-2

Climatic suitability standard: EN 60068-2-78

Humidity rating: 93 % r. h. at 40 °C

Condensation permitted?: Briefly

Vibration to standard ...: EN 60068-2-6

Clearance & creepage dist. to: EN 60664-1

Overvoltage category: II

Pollution degree clear.&creep.: 2

Protection type, housing: IP67

Mechanical data

Housing material upper part:	PBT
Connection terminal:	M12 1.4305 stainless steel
Terminal style:	screw interlocked
Height dimension:	120 mm
Width dimension:	60 mm
Depth dimension:	20 mm
Net weight:	240 g
Gross weight:	295 g
Environment	
REACH compliance:	contains min. 1 SVHC-substance
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27440108
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC002585
UNSPSC 25:	39122214
GTIN:	4046548070873
Volume:	0.402 dm3
Harmonized System Code:	85389091
Type of tariff number:	TARIC
Use of customs tariff number:	Ausfuhr, Einfuhr
Quantity per packaging unit:	1

Obligatory accessories



773612

PDP67 Connector cs VA

Optional accessories



540340

PSEN cable M12-8sf M12-8sm, 2m



540341

PSEN cable M12-8sf M12-8sm, 5m



540342

PSEN cable M12-8sf M12-8sm, 10m



540343

PSEN cable M12-8sf M12-8sm, 20m



540344

PSEN cable M12-8sf M12-8sm, 30m