




Features:

- Power supply with TopBoost, PowerBoost and configurable overload behavior
- Configurable digital signal input and output, optical status indication, function keys
- Communication interface for configuration and monitoring
- Optional connection to IO-Link, EtherNet/IP™, Modbus TCP or Modbus RTU
- Suitable for both parallel and series operation
- Natural convection cooling when horizontally mounted
- Pluggable connection technology
- Electrically isolated output voltage (SELV/PELV) per EN 61010-2-201/UL 61010-2-201
- Marker slot for WAGO marking cards (WMB) and WAGO marking strips

Technical data			
Input		Input	
Phases	1	Mains failure hold-up time	≥ 40 ms (230 VAC)
Nominal input voltage U _{i nom}	1 x 100 ... 240 VAC		
Input voltage range	1 x 90 ... 264 VAC		
Nominal mains frequency range	50 ... 60 Hz		
Input current I _i	≤ 1.3 A		
Inrush current	after 1 ms		
Power factor correction (PFC)	Active		



Output	
Nominal output voltage $U_{o\,nom}$	12 VDC (SELV)
Output voltage range	12 ... 14 VDC (adjustable)
Default Setting	12 VDC
Nominal output current $I_{o\,nom}$	10 A (12 VDC)
Nominal output power	120 W
Deviation	$\leq 1\%$
Residual ripple	$\leq 70\text{ mV}$ (peak-to-peak)
Current limitation	$1.1 \times I_{o\,nom}$ (typ.)
Overload behavior	TopBoost/PowerBoost/Time-limited constant current mode (other overload behaviors can be set)
PowerBoost	15 ADC (5 s)
TopBoost	Up to 600 %

Efficiency/Power Losses	
Power loss P_I	$\leq 0.8\text{ W}$ (standby); $\leq 1.6\text{ W}$ (no load); $\leq 10\text{ W}$ (230 VAC; nominal load)
Efficiency (typ.)	93.8 %

Signaling and Communication	
Signaling	Optical status indication (DC OK; load; warning and error states) Digital signal input and output (DI/DO)
Communications	USB (750-923 Communication Cable) Ethernet/IP™ (2789-9023 Communication Module) IO-Link (2789-9080 Communication Module) Modbus RTU (Communication Module 2789-9015) Modbus TCP (2789-9052 Communication Module)

Circuit Protection	
Internal fuse	T 6.3 A / 250 VAC
Backup fuse (recommended)	16 A (for USA/Canada: 15 A)

Safety and protection	
Isolation voltage (pri.-sec., AC)	3510 V
Isolation voltage (pri.-PE, AC)	2200 V
Isolation voltage (sec.-PE)	0.5 kVDC
Isolation voltage (sec.-signal)	0.5 kVDC
Protection class	I
Protection type	IP20; per EN 60529
Overvoltage category	III ($\leq 2000\text{ m a.s.l.}$); II ($> 2000\text{ m a.s.l.}$)
Pollution degree	2
Transient suppression (primary)	Yes
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	Yes
Series operation	Yes
MTBF	$> 1,200,000\text{ h}$ (per IEC 61709)

Connection Data	
Connection 1	
Connection type	Input/output/signaling
Connection technology	CAGE CLAMP®
WAGO connector	WAGO 721 Series
Solid conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG
Fine-stranded conductor; with insulated ferrule	2.5 ... 1.5 mm² / 12 ... 16 AWG
Fine-stranded conductor; with uninsulated ferrule	1.5 ... 0.08 mm² / 16 ... 28 AWG
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches



Physical data	
Width	35 mm / 1.378 inches
Height	130 mm / 5.118 inches
Depth from upper-edge of DIN-rail	130 mm / 5.118 inches
Note (dimensions)	Height without connector Height with connector: 166 mm

Mechanical data	
Mounting type	DIN-35 rail

Material data	
Fire load	0 MJ
Weight	650 g

Environmental requirements	
Ambient temperature (operation)	-25 ... +70 °C (Device starts at -40 °C (type-tested))
Ambient temperature (storage)	-40 ... +85 °C
Relative humidity	5 ... 96 % (no condensation permissible)
Derating	See instruction leaflet
Climatic category	3K3 (per EN 60721)
Operating altitude (max.)	5000 m

Standards and Specifications	
Conformity marking	CE
Standards/specifications	EN 61010-1 EN 61010-2-201 EN 61204-3 UL 61010-1 UL 61010-2-201 SEMI F47 UL 121201 (HazLoc)

Commercial data	
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	CN
GTIN	4066966121322
Customs tariff number	85044083900

Product Classification	
UNSPSC	39121004
ETIM 9.0	EC002540
ETIM 10.0	EC002540
ECCN	NO US CLASSIFICATION



Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Approvals / Certificates

General approvals			Declarations of conformity and manufacturer's declarations		
 					
Approval	Standard	Certificate Name	Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03080	EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081	MFD for SEMI F47 WAGO GmbH & Co. KG	-	-
UL Underwriters Laboratories Inc.	UL 61010-2-201	E255817			

Approvals for hazardous areas

		
Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc. (HAZARDOUS LOCA- TIONS)	UL 121201	E198726

Downloads

Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 2787-2134	

Documentation

Manual				Bid Text			
Product Manual Power supply; Pro 2; 1-phase; 12 VDC output voltage; 10 A output current;	V 1.0.2 18.02.2022	pdf 8079.02 KB		2787-2134	11.05.2022	xml 8.73 KB	
				2787-2134		docx 32.28 KB	



Instruction Leaflet			
Power supply; Pro 2; 1-phase; 12 VDC output voltage; 10 A output current;	V 1.0.0 03.05.2021	pdf 4316.01 KB	

Application Notes

Application Note e!COCKPIT			
e!COCKPIT Application Note WagoAppPower-Supply (a2019012)	1.1.1 06.12.2021	pdf 707.04 KB	

CAD/CAE-Data

CAD data	
2D/3D Models 2787-2134	

1 Compatible Products

1.1 Product Expansions

1.1.1 Communication Module



Item No.: 2789-9023
Communication module; EtherNet/IP; MQTT Pub/Sub; communication capability



Item No.: 2789-9080
Communication module; IO-Link; communication capability



Item No.: 2789-9015
Communication module; Modbus RTU; RJ45; communication capability



Item No.: 2789-9052
Communication module; Modbus TCP; communication capability

1.2 Optional Accessories

1.2.1 Marking

1.2.1.1 Marker carrier



Item No.: 2789-1233
Marker carrier; for WMB or marking strips; Length: 33 mm