


Data Sheet | Item Number: 2787-2144/000-070

Power supply; Pro 2; 1-phase; 24 VDC output voltage; 5 A output current; TopBoost + PowerBoost; Protection Coating; communication capability

<https://www.wago.com/2787-2144/000-070>



Features:

- Power supply with TopBoost, PowerBoost and configurable overload behavior
- Configurable digital signal input and output, optical status indication, function keys
- Communication interface for configuration and monitoring
- Optional connection to IO-Link, EtherNet/IP™, Modbus TCP or Modbus RTU
- Suitable for both parallel and series operation
- Natural convection cooling when horizontally mounted
- Pluggable connection technology



- Electrically isolated output voltage (SELV/PELV) per EN 61010-2-201/UL 61010-2-201
- Coated PCBs, resistant to flowing mixed gas per ISA S71.04:1985, G3 Group A
- Marker slot for WAGO marking cards (WMB) and WAGO marking strips

Technical data			
Input		Output	
Phases	1	Nominal output voltage $U_{o\,nom}$	24 VDC (SELV)
Nominal input voltage $U_{i\,nom}$	1 x 100 ... 240 VAC	Output voltage range	24 ... 28 VDC (adjustable)
Input voltage range	1 x 90 ... 264 VAC	Default Setting	24 VDC
Nominal mains frequency range	50 ... 60 Hz	Nominal output current $I_{o\,nom}$	5 A (24 VDC)
Input current I_i	≤ 1 A (240 VAC; nominal load); ≤ 1.8 A (100 VAC; nominal load)	Nominal output power	120 W
Inrush current	after 1 ms	Deviation	≤ 1 %
Power factor correction (PFC)	Active	Residual ripple	≤ 70 mV (peak-to-peak)
Mains failure hold-up time	≥ 20 ms (230 VAC)	Current limitation	$1.1 \times I_{o\,nom}$ (typ.)
		Overload behavior	TopBoost/PowerBoost/Time-limited constant current mode (other overload behaviors can be set)
		PowerBoost	7.5 ADC (5 s)
		TopBoost	Up to 600 %

Signaling and Communication	
Signaling	Optical status indication (DC OK; load; warning and error states) Digital signal input and output (DI/DO)
Communications	USB (750-923 Communication Cable) EtherNet/IP™ (2789-9023 Communication Module) IO-Link (2789-9080 Communication Module) Modbus RTU (Communication Module 2789-9015) Modbus TCP (2789-9052 Communication Module)

Efficiency/Power Losses	
Power loss P_i	≤ 1 W (standby); ≤ 2 W (no load); ≤ 10 W (230 VAC; nominal load)
Efficiency (typ.)	93.8 % (230 VAC; 5 A; 25 °C)

Circuit Protection	
Internal fuse	T 6.3 A / 250 VAC
Backup fuse (recommended)	16 A (for USA/Canada: 15 A)

Safety and protection	
Isolation voltage (pri.-sec., AC)	3510 V
Isolation voltage (pri.-PE, AC)	2200 V
Isolation voltage (sec.-PE)	0.5 kVDC
Isolation voltage (sec.-signal)	0.5 kVDC
Protection class	I
Protection type	IP20; per EN 60529
Protective coating	Coated PCBs
Resistance to reverse feed	≤ 35 VDC
Overvoltage category	III (≤ 2000 m a.s.l.); II (> 2000 m a.s.l.)
Pollution degree	2
Transient suppression (primary)	Yes
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	Yes
Series operation	Yes
MTBF	$> 1,000,000$ h (per IEC 61709)



Connection Data

Connection 1	
Connection type	Input/output/signaling
Connection technology	CAGE CLAMP®
WAGO connector	WAGO 721 Series
Solid conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG
Fine-stranded conductor; with insulated ferrule	2.5 ... 1.5 mm² / 12 ... 16 AWG
Fine-stranded conductor; with uninsulated ferrule	1.5 ... 0.08 mm² / 16 ... 28 AWG
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches

Physical data

Width	35 mm / 1.378 inches
Height	130 mm / 5.118 inches
Depth from upper-edge of DIN-rail	130 mm / 5.118 inches
Note (dimensions)	Height without connector Height with connector: 166 mm

Mechanical data

Mounting type	DIN-35 rail
---------------	-------------

Material data

Fire load	0 MJ
Weight	650 g

Environmental requirements

Ambient temperature (operation)	-25 ... +70 °C (Device starts at -40 °C (type-tested))
Ambient temperature (storage)	-40 ... +85 °C
Relative humidity	5 ... 96 % (no condensation permissible)
Derating	See instruction leaflet
Climatic category	3K3 (per EN 60721)
Operating altitude (max.)	5000 m

Standards and Specifications

Conformity marking	CE
Standards/specifications	EN 61010-1 EN 61010-2-201 EN 61204-3 UL 61010-1 UL 61010-2-201 DNV UL 121201 (HazLoc) ISA S71.04:1985; G3 Group A SEMI F47



Commercial data		
PU (SPU)		1 pcs
Packaging type		Box
Country of origin		CN
GTIN		4066966125931
Customs tariff number		85044083900

Product Classification		
UNSPSC		39121004
ETIM 9.0		EC002540
ETIM 10.0		EC002540
ECCN		NO US CLASSIFICATION

Environmental Product Compliance		
RoHS Compliance Status		Compliant,No Exemption

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03080
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081
UL Underwriters Laboratories Inc.	UL 61010-2-201	E255817

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
MFD for SEMI F47 WAGO GmbH & Co. KG	-	-
UK-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-

Approvals for marine applications



Approval	Standard	Certificate Name
DNV DNV GL SE	DNV-CG-0339,Aug.2021	TAA00002ZF

Approvals for hazardous areas



Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc. (HAZARDOUS LOCA- TIONS)	UL 121201	A-E198726



Downloads

Environmental Product Compliance

Compliance Search			
Environmental Product Compliance	2787-2144/000-070		

Documentation

Manual				Instruction Leaflet			
Product Manual Power supply; Pro 2; 1-phase; 24 VDC output voltage; 5 A output current	V 1.2.2 18.02.2022	pdf 7997.98 KB		WAGO Pro 2 Power Supplies	V 1.1.0 26.04.2021	pdf 4445.43 KB	

Application Notes

Application Note e!COCKPIT			
e!COCKPIT Application Note WagoAppPower-Supply (a2019012)	1.1.1 06.12.2021	pdf 707.04 KB	

CAD/CAE-Data

CAD data		CAE data	
2D/3D Models 2787-2144/000-070		EPLAN Data Portal 2787-2144/000-070	

Runtime Software

Firmware			
2787-2144, Stromversorgung; Pro 2	V 010513 13.10.2021	zip 1087.50 KB	

1 Compatible Products

1.1 Product Expansions

1.1.1 Communication Module

Item No.: 2789-9023 Communication module; EtherNet/IP; MQTT Pub/Sub; communication capability	Item No.: 2789-9080 Communication module; IO-Link; communication capability	Item No.: 2789-9015 Communication module; Modbus RTU; RJ45; communication capability	Item No.: 2789-9052 Communication module; Modbus TCP; communication capability



1.2 Optional Accessories
1.2.1 Marking
1.2.1.1 Marker carrier



[Item No.: 2789-1233](#)
Marker carrier; for WMB or marking strips;
Length: 33 mm