




Similar to illustration



- Features:**
- Power supply with TopBoost, PowerBoost and configurable overload behavior
 - Configurable digital signal input and output, optical status indication, function keys
 - Communication interface for configuration and monitoring
 - Optional connection to IO-Link, EtherNet/IP™, Modbus TCP or Modbus RTU
 - Suitable for both parallel and series operation
 - Natural convection cooling when horizontally mounted
 - Pluggable connection technology
 - Electrically isolated output voltage (SELV/PELV) per EN 61010-2-201/UL 61010-2-201
 - Marker slot for WAGO marking cards (WMB) and WAGO marking strips

Technical data			
Input		Input	
Phases	3	Inrush current	after 1 ms
Nominal input voltage $U_{in\,nom}$	3 x 400 ... 500 VAC (connection without neutral conductor)	Power factor correction (PFC)	Active
Input voltage range	3 x 340 ... 550 VAC	Mains failure hold-up time	≥ 20 ms (3 x 400 VAC)
Nominal mains frequency range	50 ... 60 Hz		
Input current I_i	≤ 3 x 0.4 A (400 VAC; 24 VDC / 5 A)		



Output	
Nominal output voltage $U_{o\,nom}$	24 VDC (SELV)
Output voltage range	24 ... 28 VDC (adjustable)
Default Setting	24 VDC
Nominal output current $I_{o\,nom}$	5 A (24 VDC)
Nominal output power	120 W
Deviation	$\leq 1\%$
Residual ripple	$\leq 70\text{ mV}$ (peak-to-peak)
Current limitation	$1.1 \times I_{o\,nom}$ (typ.)
Overload behavior	TopBoost/PowerBoost/Time-limited constant current mode (other overload behaviors can be set)
PowerBoost	7.5 ADC (5 s)
TopBoost	Up to 600 %

Efficiency/Power Losses	
Efficiency (typ.)	92.5 % (230 VAC; 5 A; 25 °C)

Signaling and Communication	
Signaling	Optical status indication (DC OK; load; warning and error states) Digital signal input and output (DI/DO)
Communications	USB (750-923 Communication Cable) Ethernet/IP™ (2789-9023 Communication Module) IO-Link (2789-9080 Communication Module) Modbus RTU (Communication Module 2789-9015) Modbus TCP (2789-9052 Communication Module)

Circuit Protection	
Pre-fuse (required)	An external DC fuse is required for the DC input voltage.
Backup fuse (recommended)	3 x 16 A (for USA/Canada: 3 x 15 A)

Safety and protection	
Isolation voltage (pri.-sec., AC)	3510 V
Isolation voltage (pri.-PE, AC)	2200 V
Isolation voltage (sec.-PE)	0.5 kVDC
Isolation voltage (sec.-signal)	0.5 kVDC
Protection class	I
Protection type	IP20; per EN 60529
Overvoltage category	III ($\leq 2000\text{ m a.s.l.}$); II ($> 2000\text{ m a.s.l.}$)
Pollution degree	2
Transient suppression (primary)	Yes
Overvoltage protection; secondary	Internal protective circuit $\leq 35\text{ VDC}$ (in the event of a fault)
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	Yes
Series operation	Yes
MTBF	$> 1,400,000\text{ h}$ (per IEC 61709)

Connection Data			
Connection 1		Connection 2	
Connection type	Input/signaling	Connection type	Output
Connection technology	CAGE CLAMP®	Connection technology	Push-in CAGE CLAMP®
WAGO connector	WAGO 721 Series	WAGO connector	WAGO 831 Series
Solid conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG	Solid conductor	0.5 ... 10 mm² / 20 ... 8 AWG
Fine-stranded conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG	Fine-stranded conductor	0.5 ... 10 mm² / 20 ... 8 AWG
Fine-stranded conductor; with insulated ferrule	0.25 ... 1.5 mm² / 20 ... 16 AWG	Fine-stranded conductor; with insulated ferrule	0.5 ... 6 mm²
Fine-stranded conductor; with uninsulated ferrule	0.25 ... 2.5 mm² / 20 ... 14 AWG	Fine-stranded conductor; with uninsulated ferrule	0.5 ... 6 mm²
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches	Strip length	13 ... 15 mm / 0.51 ... 0.59 inches



Physical data	
Width	40 mm / 1.57 inches
Height	130 mm / 5.118 inches
Depth from upper-edge of DIN-rail	130 mm / 5.118 inches
Note (dimensions)	Height without connector Height with connector: 166 mm

Mechanical data	
Mounting type	DIN-35 rail

Material data	
Fire load	0 MJ
Weight	650 g

Environmental requirements	
Ambient temperature (operation)	-25 ... +70 °C (Device starts at -40 °C (type-tested))
Ambient temperature (storage)	-40 ... +85 °C
Relative humidity	5 ... 96 % (no condensation permissible)
Derating	See instruction leaflet
Climatic category	3K3 (per EN 60721)
Operating altitude (max.)	5000 m

Standards and Specifications	
Conformity marking	CE
Standards/specifications	EN 61010-1 EN 61010-2-201 EN 61204-3 UL 61010-1 UL 61010-2-201 DNV SEMI F47 UL 121201 (HazLoc)

Commercial data	
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	CN
GTIN	4066966265941
Customs tariff number	85044083900

Product Classification	
UNSPSC	39121004
ETIM 9.0	EC002540
ETIM 10.0	EC002540
ECCN	NO US CLASSIFICATION



Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Approvals / Certificates

General approvals			Declarations of conformity and manufacturer's declarations		
 					
Approval	Standard	Certificate Name	Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03080	EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081	MFD for SEMI F47 WAGO GmbH & Co. KG	-	-
UL Underwriters Laboratories Inc.	UL 61010-2-201	UL-US-2219523-0	UK-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-

Approvals for marine applications			Approvals for hazardous areas		
					
Approval	Standard	Certificate Name	Approval	Standard	Certificate Name
DNV DNV GL SE	DNV-CG-0339,Aug.2021	TAA00002ZF	UL Underwriters Laboratories Inc. (HAZARDOUS LOCA- TIONS)	UL 121201	A-E198726

Downloads

Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 2787-2344/000-030	

Documentation

Manual				Instruction Leaflet			
Product Manual Power supply; Pro 2; 3-phase; 24 VDC output voltage; 5 A output current	V 1.0.1 15.02.2022	pdf 8129.21 KB		Stromversorgung Pro 2	V 1.1.0 03.03.2022	pdf 4607.98 KB	



CAD/CAE-Data

CAD data

2D/3D Models
2787-2344/000-030

↓

1 Compatible Products

1.1 Product Expansions

1.1.1 Communication Module



Item No.: 2789-9023
Communication module; EtherNet/IP;
MQTT Pub/Sub; communication capability



Item No.: 2789-9080
Communication module; IO-Link; commu-
nication capability



Item No.: 2789-9015
Communication module; Modbus RTU;
RJ45; communication capability



Item No.: 2789-9052
Communication module; Modbus TCP;
communication capability

1.2 Optional Accessories

1.2.1 Marking

1.2.1.1 Marker carrier



Item No.: 2789-1233
Marker carrier; for WMB or marking strips;
Length: 33 mm