

UPS-BAT/PB/24DC/40AH - Battery module



1354641

<https://www.phoenixcontact.com/pc/products/1354641>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Battery module (device with battery), VRLA-AGM, 24 V DC, 40 Ah, automatic detection and communication with QUINT UPS-IQ



Product description

For continuous monitoring and intelligent management, there is constant communication with the QUINT UPS. Thanks to automatic detection of the battery module and tool-free switching during operation, quick installation is possible. The battery modules for QUINT UPS with IQ Technology are fully charged before being sent to our warehouse.

Your advantages

- Maximum buffer times
- Consists of 2 x 12 V battery modules and an electronic monitoring unit
- Lead AGM (Absorbent Glass Mat) technology

Commercial data

Item number	1354641
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CMUEV3
GTIN	4063151686215
Weight per piece (including packing)	30,390 g
Weight per piece (excluding packing)	28,600 g
Customs tariff number	85072080
Country of origin	CN

UPS-BAT/PB/24DC/40AH - Battery module



1354641

<https://www.phoenixcontact.com/pc/products/1354641>

Technical data

Notes

General

Note on the battery	This product contains a battery with a limited shelf life that must be charged every few months. The product packaging indicates when the battery must be started up or recharged. The general shelf life can be found in the energy storage devices area under "Latest startup".
---------------------	---

Energy storage

Input

Input voltage	24 V DC (SELV)
Nominal capacity	40 Ah
Charging current	12 A
End-of-charge voltage	27.6 V (20 °C)

Output

Output current I_{\max}	45 A
Output fuse	2x 25 A
Buffer time	82 min (20 A)
	35 min (40 A)

General

Connection in parallel	yes
	max. 5
Battery type	BB Battery BP 40-12FR
Battery technology	VRLA-AGM
IQ-Technology	yes
Latest startup date (battery only)	12 Months (0 °C ... 20 °C)
Latest startup (battery only) - range	9 Months ... 12 Months (20 °C ... 30 °C) 6 Months ... 9 Months (30 °C ... 40 °C)
Accumulator module service life (according to Eurobat)	8 (20 °C)
Size designation	Block
Battery pack	yes
Suitable for fast charging	yes
Temperature sensor	yes
Number of replacement battery kits	1x (UPS-BAT-KIT/PB/2X12V/40AH (1383182))

Connection data

Conductor connection

Connection method	Push-in connection
rigid	10 mm ² ... 16 mm ² (recommended) 0.75 mm ² ... 16 mm ²

UPS-BAT/PB/24DC/40AH - Battery module



1354641

<https://www.phoenixcontact.com/pc/products/1354641>

flexible	10 mm ² ... 16 mm ² (recommended)
	0.75 mm ² ... 16 mm ²
AWG	8 ... 4 (recommended)
	20 ... 4
Stripping length	18 mm

Conductor connection

Connection method	Push-in connection
rigid	0.75 mm ² ... 16 mm ² (LIN)
flexible	0.75 mm ² ... 16 mm ² (LIN)
AWG	20 ... 4
Stripping length	18 mm

Product properties

Product family	Battery module (device with battery)
Application	for QUINT4 DC-UPS, QUINT4 AC-UPS, QUINT-UPS, and TRIO-UPS-2G
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations.

Insulation characteristics

Protection class	III
Degree of pollution	2

Dimensions

Item dimensions

Width	333 mm
Height	173 mm
Depth	199 mm

Drill hole

Diameter	5 mm
----------	------

Installation dimensions

Installation distance right/left	0 mm / 0 mm
Installation distance top/bottom	50 mm / 50 mm

Mounting

Mounting position	Horizontally, on a mounting panel
-------------------	-----------------------------------

Material specifications

Housing material	Plastic
------------------	---------

Cable/line

Battery connecting cable:

UPS-BAT/PB/24DC/40AH - Battery module



1354641

<https://www.phoenixcontact.com/pc/products/1354641>

Cable cross section	6 mm ²
Cable length	340 mm
Color	red/black

Battery connecting cable:

Cable cross section	6 mm ²
Cable length	110 mm
Color	red/black

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (storage/transport)	-20 °C ... 40 °C
Ambient temperature (charge)	0 °C ... 40 °C
Ambient temperature (discharge)	-20 °C ... 50 °C
Max. permissible relative humidity (operation)	≤ 95 %

Ex data

Suited for EX-applications	no
----------------------------	----

UPS-BAT/PB/24DC/40AH - Battery module




1354641

<https://www.phoenixcontact.com/pc/products/1354641>


Drawings

Block diagram



Block diagram

Graphic



2x: In this case, two battery modules of the same capacity are required. The data is based on an ambient temperature of +25 °C at the start of use.

 1274520 UPS-BAT/PB/24DC/1.2AH

 1274119 UPS-BAT/PB/24DC/12AH

 1474660 UPS-BAT/PB/24DC/110AH

 1274117 UPS-BAT/PB/24DC/4AH

 1348516 UPS-BAT/PB/24DC/20AH

 1274118 UPS-BAT/PB/24DC/7AH

 1354641 UPS-BAT/PB/24DC/40AH

Lead battery buffer times for QUINT DC UPS


UPS-BAT/PB/24DC/40AH - Battery module



1354641

<https://www.phoenixcontact.com/pc/products/1354641>

Graphic



The data is based on an ambient temperature of +25 °C at the start of use.

1274117 UPS-BAT/PB/24DC/4AH

1274119 UPS-BAT/PB/24DC/12AH

1354641 UPS-BAT/PB/24DC/40AH


1274118 UPS-BAT/PB/24DC/7AH

1348516 UPS-BAT/PB/24DC/20AH

1474660 UPS-BAT/PB/24DC/110AH

Lead battery buffer times for QUINT AC UPS 500 VA

Graphic



2x: There are always two battery modules of the same capacity are required. The data is based on an ambient temperature of +25 °C at the start of use.

1274117 UPS-BAT/PB/24DC/4AH

1274119 UPS-BAT/PB/24DC/12AH

1354641 UPS-BAT/PB/24DC/40AH

1274118 UPS-BAT/PB/24DC/7AH

1348516 UPS-BAT/PB/24DC/20AH

1474660 UPS-BAT/PB/24DC/110AH

Buffer times for QUINT AC UPS 1 kVA

UPS-BAT/PB/24DC/40AH - Battery module



1354641

<https://www.phoenixcontact.com/pc/products/1354641>

Graphic

Load Current	Buffertime																			
	Minutes						Hours													
	30	35	40	45	50	55	1	2	3	4	5	6	7	8	9	10	12	14	16	18
1 A																				
2 A																				
3 A																				
5 A																				
7 A																				
10 A																				
15 A																				
20 A																				

The data is based on an ambient temperature of +25 °C at the start of use.

 1348516 UPS-BAT/PB/24DC/20AH

 1354641 UPS-BAT/PB/24DC/40AH

Lead battery buffer times for TRIO DC UPS

UPS-BAT/PB/24DC/40AH - Battery module



1354641

<https://www.phoenixcontact.com/pc/products/1354641>

Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1354641>



LR

Approval ID: LR22136091TA



BV

Approval ID: 41516/B0 BV

ABS

Approval ID: 22-2244289-PDA



cULus Listed

Approval ID: E123528-20220210

DNV

Approval ID: TAA0000265

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
keine	500 V	41 A	-	- 6



IECEE CB Scheme

Approval ID: DK-124876-M1-UL



cULus Listed

Approval ID: FILE E 199827

UPS-BAT/PB/24DC/40AH - Battery module

1354641

<https://www.phoenixcontact.com/pc/products/1354641>



Classifications

ECLASS

ECLASS-13.0	27050403
ECLASS-15.0	27050403

ETIM

ETIM 10.0	EC003893
-----------	----------

UNSPSC

UNSPSC 21.0	26111700
-------------	----------

UPS-BAT/PB/24DC/40AH - Battery module

1354641

<https://www.phoenixcontact.com/pc/products/1354641>



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-l

China RoHS

Environment friendly use period (EFUP)	EFUP-25
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Diboron trioxide(CAS: 1303-86-2) Lead monoxide (lead oxide)(CAS: 1317-36-8) Lead(CAS: 7439-92-1) Diboron trioxide(CAS: 1303-86-2) Lead monoxide (lead oxide)(CAS: 1317-36-8) Lead(CAS: 7439-92-1)
SCIP	b37be338-986f-4ff6-9398-0a1cf9120f8f

EF3.1 Climate Change

CO2e kg	181.6 kg CO2e
---------	---------------

UPS-BAT/PB/24DC/40AH - Battery module



1354641

<https://www.phoenixcontact.com/pc/products/1354641>

Accessories

BATTERY MOUNTING KIT - Mounting set for securing the batteries

2320788

<https://www.phoenixcontact.com/pc/products/2320788>

Used for mounting batteries that cannot be mounted on DIN rails.



FUSE 25A/32V ATOF - Fuse

2908366

<https://www.phoenixcontact.com/pc/products/2908366>

Fuse, nominal current: 25 A, length: 19.1 mm, width: 5 mm, height: 18.8 mm



UPS-BAT/PB/24DC/40AH - Battery module



1354641

<https://www.phoenixcontact.com/pc/products/1354641>

BATTERY MOUNTING CASE - Mounting set for securing the batteries

2320458

<https://www.phoenixcontact.com/pc/products/2320458>

Used for mounting batteries that cannot be mounted on DIN rails.



UPS-BAT-KIT/PB/2X12V/40AH - Uninterruptible power supply replacement battery

1383182

<https://www.phoenixcontact.com/pc/products/1383182>

Replacement battery, VRLA-AGM, 2x12 V DC, 40 Ah



Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com