

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



TRIO DC UPS with integrated power supply, DIN rail mounting, Push-in connection, output: 24 V DC / 5 A

## Product description

The TRIO DC UPS combines an uninterruptible power supply with an integrated power supply, thereby saving space in the control cabinet. The robust solution offers comprehensive functions such as signaling, diagnostics, connection to IPCs and PLCs, and a cold restart function in a compact housing. Tool-free wiring with Push-in Technology makes handling and startup particularly easy. With the dynamic boost and intelligent battery charging behavior, the TRIO DC UPS ensures a particularly high degree of reliability. Select the appropriate TRIO battery module for your required buffer time and effortlessly create your individual complete system.

## Your advantages

- Space-saving with the combination of a UPS and power supply in a compact housing
- Easy handling ensured by tool-free wiring with Push-in connection technology
- Robust and reliable due to dynamic boost and intelligent battery charging behavior
- Direct diagnostics with multicolor LEDs and signal contacts for a clear status display

## Commercial data

Item number	1359613
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CMUD13
GTIN	4063151689964
Weight per piece (including packing)	999.8 g
Weight per piece (excluding packing)	920 g
Customs tariff number	85044095
Country of origin	CN

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

## Technical data

### Input data

Input voltage range	100 V AC ... 240 V AC -15 % ... +10 % 115 V AC ... 240 V AC $\pm 10\%$ (UL)
Voltage type of supply voltage	AC
Inrush current integral ( $I^2t$ )	typ. $< 0.5\text{ A}^2\text{s}$
Inrush current limitation	typ. $< 21\text{ A}$
Frequency range ( $f_N$ )	50 Hz ... 60 Hz $\pm 10\%$
Mains buffering time	typ. $\geq 2\text{ ms}$ (120 V AC)
Static Boost ( $I_{\text{Stat.Boost}}$ )	5 A
Switch-on time during battery operation (Bat.-Start)	$< 10\text{ ms}$
Discharge current to PE	$< 3.5\text{ mA}$
Current consumption	typ. 2.29 A (100 V AC)
Current consumption $I_N$ ( $U_N, I_{\text{OUT}} = I_N, I_{\text{charge}} = 0$ )	1.2 A (120 V AC)
Current consumption $I_{\text{max}}$ ( $U_N, I_{\text{OUT}} = I_{\text{Stat.Boost}}, I_{\text{charge}} = \text{max}$ )	2.12 A (120 V AC)
Current consumption $I_{\text{No-Load}}$ ( $U_N, I_{\text{OUT}} = 0, I_{\text{charge}} = 0$ )	0.11 A (120 V AC)
Current consumption $I_{\text{charge}}$ ( $U_N, I_{\text{OUT}} = 0, I_{\text{charge}} = \text{max}$ )	0.92 A (120 V AC)
Power consumption $P_N$ ( $U_N, I_{\text{OUT}} = I_N, I_{\text{charge}} = 0$ )	130 W (120 V AC)
Power consumption $P_{\text{max}}$ ( $U_N, I_{\text{OUT}} = I_{\text{Stat.Boost}}, I_{\text{charge}} = \text{max}$ )	248 W (120 V AC)
Power consumption $P_{\text{No-Load}}$ ( $U_N, I_{\text{OUT}} = 0, I_{\text{charge}} = 0$ )	4.3 W (120 V AC)
Power consumption $P_{\text{charge}}$ ( $U_N, I_{\text{OUT}} = 0, I_{\text{charge}} = \text{max}$ )	101 W (120 V AC)
Input fuse	6.3 A (internal (device protection))
Recommended breaker for input protection	6 A ... 16 A

### Output data

Efficiency	typ. 92.8 % (120 V AC) typ. 93.3 % (230 V AC)
Short-circuit-proof	yes
No-load proof	yes
Crest factor	typ. 1.72 (120 V AC) typ. 1.96 (230 V AC)
Switch-over time	$< 3\text{ ms}$
Output current limit	5 A
UPS connection in parallel	yes, with diode module uncoupled
UPS connection in series	no
Energy storage device connection in parallel	yes, max. 3
Energy storage device connection in series	no
Feedback voltage resistance	$\leq 35\text{ V DC}$
Protection against overvoltage at the output (OVP)	$\leq 35\text{ V DC}$
Residual ripple	$< 25\text{ mV}$
Rise time	$\leq 1\text{ s}$ ( $U_{\text{Out}} = 10\% \dots 90\%$ )

Mains operation

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

Output voltage	24 V DC
Output voltage range	24 V DC ... 28 V DC (>24 V, performance-limited) max. 120 W
Output current $I_N$	5 A
Dynamic BOOST ( $I_{Dyn.Boost}$ )	7.5 A (5 s)
Output power ( $P_N$ )	120 W
Output power ( $P_{Dyn. Boost}$ )	180 W (5 s)
Maximum no-load power dissipation	$\leq 6$ W (120 V AC) $\leq 6$ W (230 V AC)
Power loss nominal load max.	$\leq 10$ W (120 V AC) $\leq 10$ W (230 V AC)

## Battery operation

Output voltage	$U_{BAT} -0.1$ V DC
Output voltage range	19.2 V DC ... 32 V DC
Output current $I_N$	5 A
Dynamic BOOST $I_{Dyn.Boost}$ ( $I_{Dyn.Boost}$ )	7.5 A (5 s)
Output power $P_N$	120 W
Output power $P_{Dyn. Boost}$	180 W (5 s)
Output power $P_{OUT}$ ( $U_N$ , $I_{OUT} = I_{dyn.Boost}$ )	180 W (5 s)
Maximum no-load power dissipation	$\leq 1.5$ W (120 V AC) $\leq 1.5$ W (230 V AC)
Power loss nominal load max.	$\leq 2$ W (120 V AC) $\leq 2$ W (230 V AC)

## Energy storage

Nominal voltage $U_N$	24 V DC
Charging voltage	max. 32 V DC
Charging current (Preset)	1 A
Charging current (Configurable)	0.2 A ... 3 A (-25 °C ... 55 °C $\pm 5$ K)
Charging current (Reduced)	3 A ... 2.25 A (55°C ... 65°C $\pm 5$ K)
Charging current (max.)	3 A
Nominal capacity range	1.2 Ah ... 40 Ah
Battery technology	VRLA-AGM
Charge characteristic curve	$IU_0U$

## Connection data

Input	
Position	1.x
Connection technology	
Position marking	1.1 (L+), 1.2 (N-), 1.3 (PE)
Conductor connection	
Connection method	Push-in connection

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

rigid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup> 1.5 mm <sup>2</sup>
flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> 1.5 mm <sup>2</sup>
flexible with ferrule without plastic sleeve	0.25 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> 1.5 mm <sup>2</sup>
flexible with ferrule with plastic sleeve	0.25 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> 1.5 mm <sup>2</sup>
AWG	24 ... 12 16
Stripping length	10 mm

## Output

Position	2.x
----------	-----

## Connection technology

Position marking	2.1 (+), 2.2 (+), 2.3 (-), 2.4 (-)
------------------	------------------------------------

## Conductor connection

Connection method	Push-in connection
rigid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup> 1.5 mm <sup>2</sup>
flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> 1.5 mm <sup>2</sup>
flexible with ferrule without plastic sleeve	0.25 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> 1.5 mm <sup>2</sup>
flexible with ferrule with plastic sleeve	0.25 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> 1.5 mm <sup>2</sup>
AWG	24 ... 12 16
Stripping length	10 mm

## Battery

Position	4.x
----------	-----

## Connection technology

Position marking	4.1 (+), 4.2 (-)
------------------	------------------

## Conductor connection

Connection method	Push-in connection
rigid	0.2 mm <sup>2</sup> ... 10 mm <sup>2</sup> 2.5 mm <sup>2</sup>
flexible	0.2 mm <sup>2</sup> ... 6 mm <sup>2</sup> 2.5 mm <sup>2</sup>
flexible with ferrule without plastic sleeve	0.25 mm <sup>2</sup> ... 6 mm <sup>2</sup> 2.5 mm <sup>2</sup>
flexible with ferrule with plastic sleeve	0.25 mm <sup>2</sup> ... 4 mm <sup>2</sup>

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

	2.5 mm <sup>2</sup>
AWG	24 ... 8
	14
Stripping length	12 mm

## Signal

Position	3.x
----------	-----

## Conductor connection

Connection method	Push-in connection
rigid	0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
	0.5 mm <sup>2</sup>
flexible	0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
	0.5 mm <sup>2</sup>
flexible with ferrule without plastic sleeve	0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
	0.5 mm <sup>2</sup>
flexible with ferrule with plastic sleeve	0.2 mm <sup>2</sup> ... 0.75 mm <sup>2</sup>
	0.5 mm <sup>2</sup>
AWG	24 ... 16
	20
Stripping length	8 mm

## Signaling

### LED signaling

Types of signaling	LED: DC output
Function	Visualization of the operating state of the DC output voltage (DC OK)
Color	red, yellow, green (multicolor LED)
LED off	Device off (Off)
LED on (green), DC OK	Output power in operation < 90% (On (green), DC OK)
LED on (yellow), I <sub>Out</sub> > 90 %	Output power in operation > 90% (On (yellow), I <sub>Out</sub> > 90 % )
LED on (red), I <sub>SHORT</sub>	Output power overload > 150% (On (red), I <sub>SHORT</sub> )
LED on (flashing red) OVP	U <sub>OUT</sub> > OVP (Over voltage protection) (on (flashing red 50%))

### LED signaling

Types of signaling	LED: device state
Function	Visual display of the operating state of the UPS
Color	red, yellow, green (multicolor LED)
LED off	Device off (Off)
LED on (green)	Device on (on (green))
LED on (flashing green 90%)	Remote contact is short-circuited with Output (-). (on (flashing green 90%))
LED on (flashing green 10 %)	Signaling time after shutdown in battery operation (on (flashing green 10%))
LED on (yellow)	Battery operation (on (yellow))
LED on (flashing yellow)	Battery charging (on (flashing yellow 50%))

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

LED on (red)	Group alarm, device (on (red))
LED on (flashing red)	Service mode for battery (on (flashing red 50%))

## LED signaling

Types of signaling	LED: battery condition
Function	Visual display of the operating state of the battery
Color	red, yellow, green (multicolor LED)
LED off	Device off (Off)
LED on (green)	Battery SOH > 6 months (on (green))
LED on (yellow)	Battery SOH < 6 months (on (yellow))
LED on (red)	Group alarm, battery (on (red))
LED on (flashing red)	Battery SOH = 0 months (on (flashing red 50%))

## Signal input Bat.-Start

Signalization designation	Bat.-Start
Position	3.x
Position marking	3.6 (Bat.-Start)
Low signal	Connection to Output (-) with < 2.7 kΩ
High signal	Open (> 200 kΩ between Bat.-Start and Output (-))

## Signal input Remote

Signalization designation	Remote
Position	3.x
Position marking	3.7 (Remote)
Low signal	Connection to Output (-) with < 2.7 kΩ
High signal	Open (> 200 kΩ between Remote and Output (-))

## Signal input Temp.-Sensor

Signalization designation	Temp.-Sensor
Position	3.x
Position marking	3.8 (Temp.-Sensor), 3.9 (Temp.-Sensor)
Voltage	max. 3.5 V (when the sensor is not connected)
Short-circuit current rating	max. 3 mA

## Signal output DC OK

Position	3.x
Signalization designation	DC OK
Position marking	3.1 (DC OK)
State condition (Contact closed (battery operation))	$U_{Out} > 20.4 \text{ V}; U_{Out} < 32 \text{ V}$
State condition (Contact open (battery operation))	$U_{Out} < 20.4 \text{ V}; U_{Out} > 32 \text{ V}$
Switching output	Transistor output, active
Output voltage	24 V DC
Continuous load current	20 mA
LED status indicator	green (LED: DC output)

## Signal output Battery Mode

Position	3.x
----------	-----

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

Signalization designation	Bat.-Mode
Position marking	3.2 (Bat.-Mode)
State condition (Contact closed)	Device in battery mode
State condition (Contact open)	Device in mains mode or device off
Switching output	Transistor output, active
Output voltage	24 V DC
Continuous load current	20 mA
LED status indicator	yellow (LED: device state)

## Signal output

Position	3.x
Signalization designation	Bat.-Service
Position marking	3.3 (Bat.-Service)
State condition (Contact closed)	Device in battery mode
State condition (Contact open)	Device in mains mode or device off
Switching output	Transistor output, active
Output voltage	24 V DC
Continuous load current	20 mA
LED status indicator	red, flashing (LED: device status)

## Signal output Alarm

Position	3.x
Signalization designation	Alarm
Position marking	3.4 (Alarm)
State condition (Contact closed)	no alarm
State condition (Contact open)	Alarm
Switching output	Transistor output, active
Output voltage	24 V DC
Continuous load current	20 mA
LED status indicator	red (LED: battery status)

## Signal output Ready

Position	3.x
Signalization designation	Ready
Position marking	3.5 (Ready)
State condition (Contact closed (mains operation))	Battery is fully charged
State condition (Contact closed (battery operation))	As long as output voltage > cut-off voltage
State condition (Contact open (mains operation))	Battery charging
State condition (Contact open (battery operation))	Output voltage < cut-off voltage or device is switched off
Switching output	Transistor output, active
Output voltage	24 V DC
Continuous load current	20 mA

## Product properties

Product family	TRIO UPS
----------------	----------

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

MTBF (IEC 61709, SN 29500)	1229684 h (25 °C)
	749673 h (40 °C)
	353116 h (60 °C)

## Insulation characteristics

Protection class	I
Degree of pollution	2

## Dimensions

### Item dimensions

Width	68 mm
Height	135 mm
Depth	132 mm
Depth (Device depth (DIN rail mounting))	125 mm (Device depth (DIN rail mounting))

### Installation dimensions

Installation distance right/left	0 mm / 0 mm
Installation distance top/bottom	50 mm / 50 mm

## Mounting

Mounting type	DIN rail mounting
Mounting position	horizontal DIN rail NS 35, EN 60715

## Material specifications

Material (Housing front)	PS
Flammability rating according to UL 94 (housing / terminal blocks)	V0
Housing material	Aluminum

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 70 °C
Ambient temperature (operation) (Output power derating)	> 60 °C (2.5 %/K)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Maximum altitude	≤ 5000 m (≤ ↕ m DIN EN 61558-2-16)
Maximum altitude (Output power derating)	> 2000 m (10 %/1000 m)
Climatic class	3K3 (EN 60721)
Shock	18 ms, 30g, per spatial direction
Vibration (operation)	5 Hz ... 100 Hz, amplitude ±2.5 mm, 2.3g 30 Hz ... 100 Hz, 2.3g, 90 min.

## Standards and regulations

### Overvoltage category

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

EN 61010-1	III ( $\leq$ 2000 m) / II ( $\leq$ 5000 m)
EN 61010-2-201	III ( $\leq$ 2000 m) / II ( $\leq$ 5000 m)

## Safety of power supply units up to 1100 V (insulation distances)

Standard designation	Safety of power supply units up to 1100 V (insulation distances)
Standards/specifications	DIN EN 61558-2-16

## Electrical safety

Standard designation	Electrical safety
Standards/specifications	IEC 61010-2-201 (SELV)

## Electronic equipment for use in power installations

Standard designation	Equipping high voltage installations with electronic equipment
Standards/specifications	EN 50178/VDE 0160 (PELV)

## Safety for measurement, control, and laboratory equipment

Standard designation	Safety for equipment for measurement, control, and laboratory use
Standards/specifications	IEC 61010-1

## Safety extra-low voltage

Standard designation	Safety extra-low voltage
Standards/specifications	IEC 61010-1 (SELV)

## Protective extra-low voltage

Standard designation	Protective extra-low voltage
Standards/specifications	IEC 61010-2-201 (PELV)

## Safe isolation

Standard designation	Safe isolation
Standards/specifications	IEC 61010-2-201

## Limitation of harmonic line currents

Standard designation	Limitation of harmonic line currents
Standards/specifications	EN 61000-3-2

## Mains variation/undervoltage

Standard designation	Mains variation/undervoltage
Standards/specifications	SEMI F47
	EN 61000-4-11

## Approvals

UL	
Identification	UL/C-UL Listed UL 61010-1

UL	
Identification	UL/C-UL Listed UL 61010-2-201

ANSI/UL 121201

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

Identification	UL/C-UL Listed ANSI/ISA-12.12.01 Class I, Division 2, Groups A, B, C
Shipbuilding	
Identification	DNV
Shipbuilding	
Identification	LR
Shipbuilding	
Identification	Nippon Kaiji Kyokai

## EMC data

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
Low Voltage Directive	Conformance with Low Voltage Directive 2014/35/EC
Interference emission	Interference emission in accordance with EN 61000-6-3 (residential areas), EN 61000-6-4 (industrial areas) and EN 61000-6-8 (commercial areas)
Noise immunity	Immunity in accordance with EN 61000-6-2 (industrial)
Conducted noise emission	
Standards/regulations	EN 61000-6-3
Noise emission	
Standards/regulations	EN 61000-6-3
Harmonic currents	
Standards/regulations	EN 61000-3-2
Flicker	
Standards/regulations	EN 61000-3-3
Electrostatic discharge	
Standards/regulations	EN 61000-4-2
Electrostatic discharge	
Contact discharge	6 kV (Test Level 3)
Discharge in air	8 kV (Test Level 3)
Electromagnetic HF field	
Standards/regulations	EN 61000-4-3
Electromagnetic HF field	
Frequency range	80 MHz ... 6 GHz
Test field strength	10 V/m
Frequency range	1.4 GHz ... 6 GHz
Test field strength	3 V/m
Fast transients (burst)	
Standards/regulations	EN 61000-4-4

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

## Fast transients (burst)

Input	± 4 kV (100 kHz)
Output	± 2 kV (100 kHz)
Signal	± 2 kV (100 kHz)
Voltage (Battery)	± 2 kV (100 kHz)

## Surge voltage load (surge)

Standards/regulations	EN 61000-4-5
-----------------------	--------------

## Surge voltage load (surge)

Input	2 kV (Test Level 4 - symmetrical)
	4 kV (Test Level 4 - asymmetrical)
Output	1 kV (Test Level 3 - symmetrical)
	2 kV (Test Level 3 - asymmetrical)
Signal	1 kV (Test Level 2 - asymmetrical)

## Conducted interference

Standards/regulations	EN 61000-4-6
-----------------------	--------------

## Conducted interference

Frequency range	0.15 MHz ... 80 MHz
Voltage	10 V

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply




1359613

<https://www.phoenixcontact.com/pc/products/1359613>

## Drawings

Schematic diagram

### Housing



Insulation electric strength


# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

Block diagram



Block diagram

Graphic

Load Current	Buffertime												Hours					
	Minutes												Hours					
	1	2	3	5	7	8	9	10	20	30	40	45	50	1	2	3	5	8
1 A																		
2 A																		
3 A																		
5 A																		
7 A																		
10 A																		

The data is based on an ambient temperature of +25 °C at the start of use.

1394729 TRIO-BAT/PB/24DC/1.2AH

1384031 TRIO-BAT/PB/24DC/7AH

1394730 TRIO-BAT/PB/24DC/4AH

1394727 TRIO-BAT/PB/24DC/12AH

Buffer times for TRIO DC UPS for TRIO battery modules


# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

Graphic



The data is based on an ambient temperature of +25 °C at the start of use.


 1348516 UPS-BAT/PB/24DC/20AH

 1354641 UPS-BAT/PB/24DC/40AH

 1474660 UPS-BAT/PB/24DC/110 AH

Buffer times for TRIO DC UPS for lead battery module

Graphic



The data is based on an ambient temperature of +25 °C at the start of use.

 2320416 UPS-BAT/VRLA-WTR/24DC/13AH

 2320429 UPS-BAT/VRLA-WTR/24DC/26AH

Buffer times for TRIO DC UPS for VRLA-WTR battery modules

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

## Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1359613>



**cULus Listed**

Approval ID: E123528-20220128

**DNV**

Approval ID: TAA00000BM

**CoC / Compliance Statement**

Approval ID: C211-0013/25



**cULus Listed**

Approval ID: E199827-20220207

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

## Classifications

### ECLASS

ECLASS-13.0	27040705
ECLASS-15.0	27040705

### ETIM

ETIM 10.0	EC000382
-----------	----------

### UNSPSC

UNSPSC 21.0	39121000
-------------	----------

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	34, 6(c), 7(a), 7(c)-l

### China RoHS

Environment friendly use period (EFUP)	EFUP-25
An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.	

### EU REACH SVHC

REACH candidate substance (CAS No.)	Hexahydromethylphthalic anhydride(CAS: n/a)
	Lead(CAS: 7439-92-1)

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

## Mandatory accessories

### TRIO-BAT/PB/24DC/1.2AH - Battery module

1394729

<https://www.phoenixcontact.com/pc/products/1394729>

Battery module (device with battery), VRLA-AGM, 24 V DC, 1.2 Ah



### TRIO-BAT/PB/24DC/4AH - Battery module

1394730

<https://www.phoenixcontact.com/pc/products/1394730>

Battery module (device with battery), VRLA-AGM, 24 V DC, 4 Ah



# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

## TRIO-BAT/PB/24DC/7AH - Battery module

1384031

<https://www.phoenixcontact.com/pc/products/1384031>

Battery module (device with battery), VRLA-AGM, 24 V DC, 7 Ah




## TRIO-BAT/PB/24DC/12AH - Battery module

1394727

<https://www.phoenixcontact.com/pc/products/1394727>

Battery module (device with battery), VRLA-AGM, 24 V DC, 12 Ah



# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

## UPS-BAT/PB/24DC/20AH - Battery module

1348516

<https://www.phoenixcontact.com/pc/products/1348516>

Battery module (device with battery), VRLA-AGM, 24 V DC, 20 Ah, automatic detection and communication with QUINT UPS-IQ



---

## UPS-BAT/PB/24DC/40AH - Battery module

1354641

<https://www.phoenixcontact.com/pc/products/1354641>

Battery module (device with battery), VRLA-AGM, 24 V DC, 40 Ah, automatic detection and communication with QUINT UPS-IQ



---

## Accessories

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

## UWA 182/52 - Mounting adapter

2938235

<https://www.phoenixcontact.com/pc/products/2938235>



Universal wall adapter for securely mounting the device in the event of strong vibrations. The device is screwed directly onto the mounting surface. The universal wall adapter is attached on the top/bottom.

---

## SZS 0,4X2,5 VDE - Screwdriver

1205037

<https://www.phoenixcontact.com/pc/products/1205037>



Screwdriver, slot-headed, VDE insulated, size: 0.4 x 2.5 x 80 mm, 2-component grip, with non-slip grip

# TRIO3-UPS/1AC/24DC/5 - Uninterruptible power supply



1359613

<https://www.phoenixcontact.com/pc/products/1359613>

## POTI SEALING PLUG - Sealing plug

1175957

<https://www.phoenixcontact.com/pc/products/1175957>



Sealing plug for protection against manipulation (adjustment of the DC output voltage) by sealing off the potentiometer opening

---

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

[info@phoenixcontact.com](mailto:info@phoenixcontact.com)