

QUINT-BAT/24DC/ 7.2AH - Battery module



2866352

<https://www.phoenixcontact.com/pc/products/2866352>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Battery module, lead AGM, VRLA technology, 24 V DC, 7.2 Ah. Connection via pin cable lug, 14 mm.

Product description

QUINT-BAT – battery module with lead AGM technology for maximum buffer times.

Commercial data

Item number	2866352
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CMUEV3
GTIN	4017918959753
Weight per piece (including packing)	6,968.5 g
Weight per piece (excluding packing)	6,000 g
Customs tariff number	85072080
Country of origin	CN

QUINT-BAT/24DC/ 7.2AH - Battery module



2866352

<https://www.phoenixcontact.com/pc/products/2866352>

Technical data

Notes

General

Note on the battery	This product contains a battery with a limited shelf life that must be charged every few months. The product packaging indicates when the battery must be started up or recharged. The general shelf life can be found in the energy storage devices area under "Latest startup".
---------------------	---

Input data

Input voltage	24 V DC
---------------	---------

Output data

Nominal output voltage	24 V DC
Output current $I_{\max}$	50 A
Output fuse	2x 25 A
Connection in parallel	yes, for increasing the buffer period
Connection in series	no

Battery operation

Nominal output voltage	24 V DC
Nominal output current (I_N)	50 A

Energy storage

Nominal capacity	7 Ah
Battery module service life	6 Years ... 9 Years (20 °C)
Latest startup date (battery only)	9 Months (20 °C ... 30 °C)
	6 Months (30 °C ... 40 °C)
Battery technology	VRLA-AGM
Memory medium	7 Ah battery
Number of cells	2
Size designation	Block
Battery pack	yes
IQ technology	no
Suitable for fast charging	yes

Product properties

Product family	Battery module (device with battery)
Application	for QUINT DC-UPS 20A/40A
IQ technology	no

Insulation characteristics

Protection class	III
------------------	-----

QUINT-BAT/24DC/ 7.2AH - Battery module



2866352

<https://www.phoenixcontact.com/pc/products/2866352>

Dimensions

Width	164 mm
Height	156 mm
Depth	110 mm

Material specifications

Housing material	Metal
Type of housing	Steel sheet, zinc-plated

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	0 °C ... 40 °C

Approvals

Shipbuilding approval	DNV GL (EMC A)
-----------------------	----------------

Ex data

Suited for EX-applications	no
----------------------------	----

QUINT-BAT/24DC/ 7.2AH - Battery module


2866352

<https://www.phoenixcontact.com/pc/products/2866352>



Drawings

Block diagram



QUINT-BAT/24DC/ 7.2AH - Battery module



2866352

<https://www.phoenixcontact.com/pc/products/2866352>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/2866352>



EAC

Approval ID: RU S-DE.BL08.W.00764



EAC

Approval ID: RU*DE*01.B.78948/21

DNV

Approval ID: TAA00002EW

QUINT-BAT/24DC/ 7.2AH - Battery module



2866352

<https://www.phoenixcontact.com/pc/products/2866352>

Classifications

ECLASS

ECLASS-13.0	27050403
ECLASS-15.0	27050403

ETIM

ETIM 10.0	EC003893
-----------	----------

UNSPSC

UNSPSC 21.0	26111700
-------------	----------

QUINT-BAT/24DC/ 7.2AH - Battery module



2866352

<https://www.phoenixcontact.com/pc/products/2866352>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-3
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	d913a37f-5b27-4b30-84d4-c1f18bdb37a0

EF3.1 Climate Change

CO2e kg	17.3 kg CO2e
---------	--------------

QUINT-BAT/24DC/ 7.2AH - Battery module

2866352

<https://www.phoenixcontact.com/pc/products/2866352>



Accessories

QUINT-ADAPTER/4 - Mounting adapter

2866857

<https://www.phoenixcontact.com/pc/products/2866857>

Assembly adapter for QUINT-BAT/24DC... on 35mm rail



UPS-BAT-KIT/PB/2X12V/7AH - Uninterruptible power supply replacement battery

1283119

<https://www.phoenixcontact.com/pc/products/1283119>

Replacement battery, VRLA-AGM, 2x12 V DC, 7 Ah



QUINT-BAT/24DC/ 7.2AH - Battery module

2866352

<https://www.phoenixcontact.com/pc/products/2866352>



FUSE 25A/32V ATOF - Fuse

2908366

<https://www.phoenixcontact.com/pc/products/2908366>



Fuse, nominal current: 25 A, length: 19.1 mm, width: 5 mm, height: 18.8 mm

Phoenix Contact 2026 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com