

**Features:**

- Charger and controller for uninterruptible power supply (UPS)
- Current and voltage monitoring, as well as parameter setting via LCD and RS-232 interface
- Active signal outputs for function monitoring
- Remote input for deactivating the buffered output
- Input for temperature control of connected battery
- Battery control (from manufacturing no. 215563 onwards) detects both battery life and battery type

Technical data

Input	
Nominal input voltage $U_{i\text{nom}}$	24 VDC
Input voltage range	22 ... 29 VDC
Nominal mains frequency range	0 Hz
Input current I_i	≤ 0.1 A (no load); ≤ 0.8 A (charging); ≤ 10.8 A
Inrush current	no load

Output	
Nominal output voltage $U_{o\text{nom}}$	24 VDC
Output voltage range	$U_o - 1$ VDC (rated operation); 20 ... 25.5 VDC (buffer mode)
Nominal output current $I_{o\text{nom}}$	10 A
Current limitation	$1.1 \dots 1.4 \times I_{o\text{nom}}$ (typ.)

Energy storage systems

Buffer time	10 s ... 10 min or constant; adjustable
Switch-on threshold	DC 20 ... 25.5 V (adjustable)
Memory type	Lead-acid fleece
Charging current	≤ 0.6 A
End-of-charge voltage	26 ... 29.5 VDC (temperature-controlled; optional fixed setting)
Recommended battery module	787-871, 787-872, 787-873, 787-876, 787-1671

Signaling and Communication

Signaling	1 x DC OK LED (green) 1 x Warning LED (yellow) 1 x Error LED (red) LCD 3 x Signal output (24 VDC; max. 25 mA) 1 x Isolated relay contact (max. 30 VDC; 1 A) 1 x RS-232 interface Battery control (C+; C-)
Operation status indicator	Green LED (U_o) Yellow LED (warning) Red LED (error)
Communications	RS-232 serial interface
Remote input	Switching buffer mode off

Efficiency/Power Losses		Circuit Protection	
Power loss P_1	$\leq 15 \text{ W}; \leq 20 \text{ W}$ (nominal load)	Internal fuse	T 15 A
Efficiency (typ.)	95 %		
Safety and protection			
Isolation voltage (connectors – housing)	0.5 kVDC		
Protection class	III		
Protection type	IP20; per EN 60529		
Reverse voltage protection	Yes		
Resistance to reverse feed	$\leq 35 \text{ VDC}$		
Pollution degree	2		
Parallel operation	Yes, max. 3 battery modules for buffer time extension (temperature measurement evaluation is only possible via one battery module)		
Series operation	No		
MTBF	$> 500,000 \text{ h}$ (per IEC 61709)		
Connection Data			
Cable length (max.)	3 m (input, output, battery control)	Connection 1	
		Connection type	Input/output
		Connection technology	CAGE CLAMP®
		WAGO connector	WAGO 231 Series
		Solid conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG
		Fine-stranded conductor	0.08 ... 2.5 mm² / 28 ... 12 AWG
		Strip length	8 ... 9 mm / 0.31 ... 0.35 inches
Connection 2			
Connection type	Signaling		
Connection technology	CAGE CLAMP®		
WAGO connector	WAGO 733 Series		
Solid conductor	0.08 ... 0.5 mm² / 28 ... 20 AWG		
Fine-stranded conductor	0.08 ... 0.5 mm² / 28 ... 20 AWG		
Strip length	5 ... 6 mm / 0.2 ... 0.24 inches		
Physical data			
Width	40 mm / 1.575 inches		
Height	163 mm / 6.417 inches		
Depth from upper-edge of DIN-rail	163 mm / 6.417 inches		
Note (dimensions)	Height with connector		
Mechanical data			
Mounting type	DIN-35 rail		

Material data

Fire load	0 MJ
Weight	800 g

Environmental requirements

Ambient temperature (operation)	-10 ... +60 °C
Ambient temperature (storage)	-25 ... +85 °C
Relative humidity	5 ... 96 % (no condensation permissible)

Standards and Specifications

Conformity marking	CE
Standards/specifications	EN 61010-1 EN 61010-2-201 UL 60950 UL 508 EN 61000-6-2 EN 61000-6-3

Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454909857
Customs tariff number	85044060900

Product Classification

UNSPSC	39121006
eCl@ss 10.0	27-04-06-90
eCl@ss 9.0	27-04-06-90
ETIM 9.0	EC000382
ETIM 10.0	EC000382
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates**General approvals****Declarations of conformity and manufacturer's declarations**

Approval	Standard	Certificate Name
EAC	TP TC 020/2011	EAC CoC 03081
GZO Almaty Standard		
UL Underwriters Laboratories Inc.	UL 508	E255817
UR Underwriters Laboratories Inc.	UL 60950-1	E255815

Approval	Standard	Certificate Name
EU-Declaration of Confor- mity	-	-
WAGO GmbH & Co. KG		
UK-Declaration of Confor- mity	-	-
WAGO GmbH & Co. KG		

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 787-870



Documentation

Quick-Start Guide

Quickstart for Software
759-870

V 1.0.0
pdf
3043.43 KB



Bid Text

787-870
12.07.2019
xml
7.79 KB



787-870
12.07.2019
docx
22.98 KB



ausschreiben.de
787-870



Instruction Leaflet

Uninterruptible power
supply

27.04.2020

pdf
1264.21 KB



CAD/CAE-Data

CAD data

2D/3D Models 787-870



CAE data

EPLAN Data Portal
787-870



WSCAD Universe
787-870



ZUKEN Portal 787-870



Engineering-Software

Configuration and Commissioning Software

WAGO UPS Shutdown
Tool

4.13
18.11.2021

exe
48463.53 KB



WAGO Software
759-870

4.13
10.05.2021

zip
38762.69 KB



Libraries

Library

Anbindung Stromversorgungen Serie 787

1.3.0
14.05.2014zip
549.48 KB

1 Compatible Products

1.1 Optional Accessories

1.1.1 Cables and connectors

1.1.1.1 Communication cable

[Item No.: 787-890](#)

RS-232 communication cable; Length 1.8 m

1.1.1.2 Connecting cable

[Item No.: 761-9005](#)

USB adapter; with 1m connection cable

1.1.2 Marking

1.1.2.1 Marking strip

[Item No.: 2009-110](#)

Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white

[Item No.: 210-831](#)

Marking strips; on reel; 2.3 mm wide; plain; Self-adhesive; white

[Item No.: 210-832](#)

Marking strips; on reel; 3 mm wide; plain; Self-adhesive; white

1.1.3 Mounting adapter

1.1.3.1 DIN-rail adapter

[Item No.: 787-897](#)

Carrier rail adapter made of zinc die-cast; for mounting 787-8xx devices to a DIN 35 rail; gray

[Item No.: 787-896](#)

Carrier rail adapter; for mounting 787-8xx devices to a DIN 35 rail; gray

1.1.3.2 Wall-mount adapter

[Item No.: 787-895](#)

Mounting carrier; for screw fixing of 787-8xx devices on mounting plate or wall without DIN 35 rail; gray

1.1.4 Power supply

1.1.4.1 Uninterruptible power supply



[Item No.: 787-871](#)

Lead-acid AGM battery module; 24 VDC input voltage; 20 A output current; 3.2 Ah capacity; with battery control

[Item No.: 787-873](#)

Lead-acid AGM battery module; 24 VDC input voltage; 40 A output current; 12 Ah capacity; with battery control

[Item No.: 787-872](#)

Lead-acid AGM battery module; 24 VDC input voltage; 40 A output current; 7 Ah capacity; with battery control

[Item No.: 787-1671](#)

Lead-acid AGM battery module; 24 VDC input voltage; 5 A output current; Capacity: 0.8 Ah; with battery control



[Item No.: 787-876](#)

Lead-acid AGM battery module; 24 VDC input voltage; 7.5 A output current; 1.2 Ah capacity; with battery control

1.1.5 Tool

1.1.5.1 Operating tool



[Item No.: 210-719](#)

Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft

[Item No.: 210-720](#)

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured