


## Data Sheet | Item Number: 286-352/004-000


Relay module; Nominal input voltage: 24 VDC; 4 make contacts; Limiting continuous current: 5 A; Railway; Red status indicator; Module width: 25 mm; gray

<https://www.wago.com/286-352/004-000>



Color: ■ gray

Similar to illustration



### Technical data

#### Control circuit

Nominal input voltage $U_N$	24 VDC
Input voltage range	-30 ... +25 %
Nominal input current at $U_N$	9 mA

#### Load circuit

Number of make/switch-on contacts	4
Contact material (relay)	AgNi + Au
Limiting continuous current	5 A
Switching Voltage, Max.	250 VAC
Pull-in time (typ.)	10 ms
Drop-out time (typ.)	5 ms
Bounce time (typ.)	2 ms

### Safety and protection

Rated Voltage	250 V
Rated impulse withstand voltage	2.5 kV
Pollution degree	2
Dielectric strength (control/load circuit) (AC, 1 min)	1.5 kVrms
Protection type	IP20

### Physical data

Width	25 mm / 0.984 inches
Height	52 mm / 2.047 inches
Depth from upper-edge of DIN-rail	82.5 mm / 3.248 inches
Note (dimensions)	Depth including carrier terminal block

### Mechanical data

Mounting type	Pluggable module for receptacle terminal blocks
---------------	---

### Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	gray
Fire load	14.884 MJ
Weight	40.1 g

### Environmental requirements

Ambient temperature (operation at $U_N$ )	-25 ... +70 °C
Ambient temperature (storage)	-25 ... +70 °C
Processing temperature	-25 ... +50 °C
Relative humidity	5 ... 85 % (no condensation permissible)
Operating altitude (max.)	2000 m

### Standards and Specifications

Standards/specifications	EN 60664-1
--------------------------	------------

### Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
PU (SPU)	10 (1) pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143104760
Customs tariff number	85364900990

### Product Classification

UNSPSC	39122334
eCl@ss 10.0	27-37-16-01
eCl@ss 9.0	27-37-16-01
ETIM 9.0	EC001437
ETIM 10.0	EC001437
ECCN	NO US CLASSIFICATION

### Environmental Product Compliance

CAS-No.	1303-86-2 7439-92-1 79-94-7
REACH Candidate List Substance	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol Diboron trioxide Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c) 7(a)
SCIP notification number (Austria)	bf930b2d-e357-465c-96d7-3e8b0bf89a2b
SCIP notification number (Belgium)	bc2ec3b4-0412-48bd-ad5a-ecd39196622d
SCIP notification number (Bulgaria)	2cb282cd-cb32-42b2-8779-4fc429e12ee1
SCIP notification number (Czech Republic)	1452ea77-3381-49c2-bacd-0c4f0ca3b2ac
SCIP notification number (Denmark)	d9ee84a9-3db0-4341-abd7-ca0c21680530
SCIP notification number (Finland)	0237c6af-7920-44d7-8b0d-81311cd6108b
SCIP notification number (France)	d16fcd46-55d1-4de7-8287-7304e4eb1ade
SCIP notification number (Germany)	1f1f3731-59f5-4065-b4e7-c49b165fb577
SCIP notification number (Hungary)	87cee33c-de33-4603-b146-70b65247a0f4
SCIP notification number (Italy)	f25e43d5-92e9-43f4-82ea-4dc5d836247b
SCIP notification number (Netherlands)	52650da2-2998-46ec-9897-d3d91b1a5fae
SCIP notification number (Poland)	4e8bd6a1-1551-4be2-9d73-5c561605e082
SCIP notification number (Romania)	3653fb6d-9806-484e-9bbd-2ed40d1bdd7f
SCIP notification number (Sweden)	3f5e52e7-3e95-402e-b70d-4fbfa9d9fc49

### Approvals / Certificates

#### General approvals



Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03078

**Downloads**

**Environmental Product Compliance**

<b>Compliance Search</b>			
Environmental Product Compliance			↓
286-352/004-000			

**Documentation**

<b>Bid Text</b>			
286-352/004-000	19.02.2019	xml 3.82 KB	↓
286-352/004-000	27.03.2015	doc 26.50 KB	↓

<b>Instruction Leaflet</b>			
Operation and Assembly Instructions Interface	V 1.0.0 02.04.2025	pdf 1246.19 KB	↓

**CAD/CAE-Data**

<b>CAE data</b>	
WSCAD Universe	↓
286-352/004-000	

**1 Compatible Products**

**1.1 Optional Accessories**

**1.1.1 Marking**

**1.1.1.1 Marker**



**Item No.: 209-701**  
 WSB marking card; as card; not stretchable; plain; snap-on type; white

**1.1.2 Terminal blocks**

**1.1.2.1 Terminal block for pluggable modules**



**Item No.: 280-639**  
 Terminal block for pluggable modules; 10-pole; with 2-conductor terminal blocks; with orange separator; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; CAGE CLAMP®; 2,50 mm<sup>2</sup>; gray



**Item No.: 280-765**  
 Terminal block for pluggable modules; 10-pole; with 4-conductor terminal blocks; with marker carrier; with orange separator; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; CAGE CLAMP®; 2,50 mm<sup>2</sup>; gray



**Item No.: 280-629**  
 Terminal block for pluggable modules; 10-pole; with 4-conductor terminal blocks; with orange separator; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; CAGE CLAMP®; 2,50 mm<sup>2</sup>; gray

## Installation Notes

### Installation



Coding ensures correct polarity.



Pluggable electronic modules on 2- or 4-conductor carrier terminal blocks

### Marking



Marking via WMB Multi Marking System.

### Testing



Function testing via touch-proof test slots