

Continuous Hinge Two-Door with Handle Type 12



Ideal for larger wall-mount applications requiring ease of installation and access to full-width internal panel. Overlapping door design allows easy access in areas with minimal aisle space.

INDUSTRY STANDARDS

UL 508A Listed; Type 12; File No. E61997

cUL Listed per CSA C22.2 No. 94; Type 12; File No. E61997

NEMA/EEMAC Type 12

IEC 60529, IP55

FEATURES

Seams continuously welded and ground smooth

External welded-on mounting brackets for easy installation

External formed body flange channels away liquids

Gasketed overlapping doors eliminate need for center post

Removable door with continuous hinge

Oil-tight key-locking handle with 3-point latch

Removable heavy gauge continuous hinge pin

Data pocket is high-impact thermoplastic

Collar studs for mounting optional panels

Bonding provision on both doors

Body is white inside with ANSI 61 grey finish outside

Door is ANSI 61 grey inside and outside

SPECIFICATIONS

Exterior Color Code:	ANSI 61
Exterior Color:	Gray
Material:	Mild Steel
Finish:	Powder Coated
Interior Color:	White

Table 1/1

Catalog Number	Article Number	Height	Width	Depth	Thickness	Stiffener Body
A484812WFLP	27650	48in	48in	12in	14ga	0
A304810WFLP	27150	30in	48in	10in	16ga	0
A306010WFLP	27160	30in	60in	10in	16ga	0
A304210WFLP	27140	30in	42in	10in	16ga	0
A364212WFLP	27190	36in	42in	12in	16ga	0
A364812WFLP	27170	36in	48in	12in	16ga	0
A244808WFLP	27130	24in	48in	8in	16ga	0
A366012WFLP	27180	36in	60in	12in	16ga	0
A244208WFLP	27120	24in	42in	8in	14ga	0
A426012WFALP	27210	42in	60in	12in	14ga	1
A424812WFLP	27640	42in	48in	12in	14ga	3
A424212WFLP	27630	42in	42in	12in	14ga	3

ADDITIONAL PRODUCT DETAILS

Purchase panels separately. Optional stainless steel, conductive, composite and aluminum panels are available for most sizes.

A484812WFLP back is 10 gauge.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE