

Stainless Steel Wallmount 2 Door 3 Point Latch Type 4X



These two-door wallmount enclosures provide industry-leading protection for components in corrosive or wet environments. Enclosures have a removable centerpost for easy panel installation, 3-point latching with HOFFMAN's exclusive PowerGlide Handles, and a seamless foam-in-place gasket for sealing protection from contaminants.

INDUSTRY STANDARDS

UL 508A Listed; Type 3R, 4, 4X, 12; File No. E61997

cUL Listed per CSA C22.2 No 94; Type 3R, 4, 4X, 12; File Number E61997

NEMA Type 3, 3R, 4, 4X, 12, 13

IEC 60529, IP66

Meets NEMA Type 3RX requirements

FEATURES

Seams continuously welded and ground smooth

Removable centerpost for easy panel installation

Flange trough collar around all sides of enclosure door openings

External mounting brackets

Heavy-duty 3-point latching mechanism operated by Type 316 stainless steel PowerGlide padlocking handles

Easily removable doors by pulling heavy gauge continuous hinge pin

Data pocket is high-impact thermoplastic

Seamless foam-in-place gasket

Collar studs provided for mounting optional panels

Bonding provisions on doors; grounding studs on body

Thickness: 14ga
Finish: Brushed #4
Material: Stainless Steel 304



SPECIFICATIONS

Catalog Number	Article Number	Height	Width	Depth
A30H4210WFSSLP3PT 	14522	30in	42in	10in
A24H4808WFSSLP3PT 	14521	24in	48in	8in
A42H4212WFSSLP3PT 	14528	42in	42in	12in
A36H6012WFSSLP3PT 	14527	36in	60in	12in
A42H4812WFSSLP3PT 	14531	42in	48in	12in
A36H4812WFSSLP3PT 	14526	36in	48in	12in
A24H4208WFSSLP3PT 	14518	24in	42in	8in
A36H4212WFSSLP3PT 	14525	36in	42in	12in
A42H6012WFSSALP3PT 	14532	42in	60in	12in
A30H4810WFSSLP3PT 	14523	30in	48in	10in
A30H6010WFSSLP3PT 	14524	30in	60in	10in
A48H4812WFSSLP3PT  	14533	48in	48in	12in

ADDITIONAL PRODUCT DETAILS

Purchase panels separately. Optional stainless steel panels are available for most sizes.

Enclosure backs for A42H4212WFSSLP3PT, A42H4812WFSSLP3PT and A42H6012WFSSALP3PT have internal stiffeners.

A48H4812WFSSLP3PT is 14 gauge with a 12 gauge back.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE