

WeatherFlo Flange Mount Disconnect with Fan Type 3R, 47x26x14, White, Mild Steel

CATALOG NUMBER

WFD40LP

WeatherFlo Flange Mount Disconnect Enclosures feature a forced-air ventilation system for cooling drives or other high-heat producing equipment in outdoor applications.

INDUSTRY STANDARDS

UL 508A Listed; Type 3R; File Number E61997

cUL Listed per CSA C22.2 No 94; Type 3R; File Number E61997

NEMA/EEMAC Type 3R

IEC 60529, IP32



FEATURES

Flange Mount Disconnect mounting provision present

White polyester powder finish with low solar absorption

Integrated solar shield top and intake cover

Adjustable thermostat; 70-140 F (21-60 C)

Active cooling ventilation system with factory-installed fan(s) and washable, metal filters (115 VAC fans)

Terminal power connection for fan(s)

Easily accessible and washable metal filters

Adjustable thermostat; 70-140 °F (21-60 °C)

Lift-off, hinged door

Three-point latching with stainless handle

External mounting brackets

Collar studs provided for panel mounting, panel sold separately

Grounding provision on door and body

Gasketed door

PRODUCT ATTRIBUTES

Article Number: 60768

Height: 47in

Width: 26in

Depth: 14in

Material: Mild Steel

Finish: Powder Coated

Color: Signal White

Color Code: RAL 9003

Thickness: 14ga

Drive HorsePower: 40HP

Weight: 168lb

ADDITIONAL PRODUCT DETAILS

Purchase panels separately.

WFD75LP, WFD100LP, and WFD100PLP are constructed from 0.100 inch (2.5mm) Aluminum

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE