Data sheet

BRP 230VAC 1CO

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



General ordering data

Version	QCR-SERIES, Relay module, Number of contacts: 1, x 1 CO Contact AgSnO, Rated control voltage: 230 V AC, Continuous current: 6 A, PUSH IN, Test button available: No
Order No.	3162370000
Type	BRP 230VAC 1CO
GTIN (EAN)	4099987790024
Qty.	20 items

Data sheet

BRP 230VAC 1CO

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

Approvals	CE
ROHS	Conform

Dimensions and weights

Depth	58 mm	Depth (inches)	2.2835 inch
Height	88 mm	Height (inches)	3.4646 inch
Width	6.1 mm	Width (inches)	0.2402 inch
Net weight	25 g		

Temperatures

Storage temperature	-40 °C...85 °C	Ambient temperature	-40 °C...60 °C
Operating temperature		Humidity	5-95% relative humidity, Tu = 40°C, without condensation

Control side

Rated control voltage	230 V AC	Rated current AC	7.1 mA
Status indicator	Red LED		

Load side

Rated switching voltage	250 V AC / 30 V DC	Max. switching frequency at rated load	0.1 Hz
Max. switching current	6 A	Max. switching voltage, AC	250 V
Max. switching voltage, DC	30 V	AC switching capacity (resistive), max.	6A
Switch-on delay	<25 ms	Switch-off delay	<25 ms
Min. switching current	100 mA	Contact type	1 x 1 CO Contact (AgSnO)
Mechanical service life	10 x 106 switching cycles	Min. switching power	100 mA / 5 V DC

General data

Operating altitude	≤ 2000 m	Mounting rail	TS 35
Test button available	No	Mechanical switch position indicator	No
Colour	black	UL 94 flammability rating	V-0

Insulation coordination

Insulation coordination	Surge voltage category	III
Insulation coordination according to	EN/IEC 61010-1	
Rated voltage	230 V	
Pollution severity	2	
Surge voltage category	III	
Dielectric strength for control side - load side	4 kVeff / 1 min	
Dielectric strength of open contact	1 kVeff / 1 min	
Impulse withstand voltage at input and output	6 kV (1.2/50 µs)	
Protection degree	IP20	

BRP 230VAC 1CO

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Connection data

Wire connection method	PUSH IN

Classifications

ETIM 8.0	EC001437	ETIM 9.0	EC001437
ETIM 10.0	EC001437	ECLASS 14.0	27-37-16-01
ECLASS 15.0	27-37-16-01		